

Sewing Pattern — Blouse 4379

Recommendations on fabric: natural or mixed dress fabric

You will also need: 6 buttons, fusible interfacing

If the pattern has a double line around it, the seam allowances are included.

Note: By default, seam allowances are NOT included (single line) and will need to be added when laying out and cutting details.

Seam Allowance: all seams - 1 cm; on hem of the blouse –1.5 cm

Attention! First of all, please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to take into account pieces to be duplicated or cut on a fold.

When sewing the garment, pay attention to notches. They must match up with corresponding pieces.



CUTTING:

The word, “beam” used on some patterns means “straight of grain”. Some pieces will be cut on the fold, this is noted on the pattern piece. Mark all notches and other design features such as darts, pleats etc. from the pattern onto your fabric.

Darts: The fold of the dart is always pressed toward the center of your garment, or down toward the hem.

Main fabric:

1. Center front - cut 2
2. Side front - cut 2
3. Center back —cut 2
4. Side back — cut 2
5. Front sleeve – cut 2
6. Back sleeve — cut 2
7. Collar —cut 2
8. Collar-stand — cut 2

Fusible interfacing:

1. Collar — cut 1
2. Collar-stand - cut 1

INSTRUCTIONS:

1. Apply fusible interfacing to front self-plackets, outer collar and inner collar-stand.
2. Pin collars right sides together, sew outer edges. Clip into curves. Turn collar right side out, straighten and press. Pin collar-stands right sides together, inserting ready collar between them, match notches and sew, stitching ends of collar-stand at the same time. Start and end stitch exactly near marked line of collar-stand connecting seam. Turn ready collar out and press.
3. Sew darts on back. Press darts toward center. Sew side backs to center backs. Serge and press the seams toward center. Sew center back seam. Serge and press seam toward left.
4. Make pleats on front neckline and sew from top edge at 4 cm. Sew side fronts to center fronts. Serge and press the seam toward center.
5. Right front: Press front inside onto wrong side along front edge (krai borta) and hidden placket front edge lines (krai borta potainoi zastezhki planki). Make a decorative stitch along inner edge of placket at 3 cm from the front edge. Turn inner part of placket toward front edge and press. Make buttonholes on right front. Left front: Turn closure placket inside first at 1 cm, and then at 3 cm and make a decorative stitch along inner edge of placket.
6. Sew shoulder and side seams, serge, and press seams toward back.
7. Sew outer collar-stand with collar into the neckline, turn open edge of inner collar-stand under, and topstitch into outer collar-stand connecting seam.
8. Sew sleeve seam. Serge and press toward back. Serge lower edges of front and back sleeves, turn onto wrong side and topstitch. Baste back sleeve onto front sleeve along top edge according to marks. Make a gathering stitch along sleeve cap for ease. Sew in sleeve, matching notches and adjusting ease. Serge seam allowances.
9. Serge lower edge of garment, press onto wrong side, and topstitch.
10. Sew buttons on left front according to buttonholes.

TECHNICAL DRAWING: