

Sewing Pattern — Dress 4382

Recommendations on fabric: fabric suitable for dresses

You will also need: fusible interfacing; 5 buttons

If the pattern has a double line around it, the seam allowances are included.

Note: By default, seam allowances are NOT included (single line) and will need to be added when laying out and cutting details.

Seam Allowance: on hem — 2 cm, all other seams - 1 cm

Attention! First of all, please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to take into account pieces to be duplicated or cut on a fold.

When sewing the garment, pay attention to notches. They must match up with corresponding pieces.



CUTTING:

The word, “beam” used on some patterns means “straight of grain”. Some pieces will be cut on the fold, this is noted on the pattern piece. Mark all notches and other design features such as darts, pleats etc. from the pattern onto your fabric.

Darts: The fold of the dart is always pressed toward the center of your garment, or down toward the hem.

Main fabric:

1. Upper back – cut 1
2. Lower back – cut 1
3. Center upper right front — cut 1
4. Center upper left front — cut 1
5. Side upper front — cut 2
6. Lower front — cut 1
7. Yoke — cut 1
8. Sleeve — cut 2
9. Stand-up collar — cut 2
10. Left front band facing — cut 1
11. Cuff — cut 2
12. Belt — cut 1

Interfacing:

1. Stand-up collar — cut 1
2. Front band facing— 2 details

INSTRUCTIONS:

1. Apply interfacing to details.
2. Fold right front inside, matching lines «button stand edge» and « button stand edge of hidden placket». Turn inner part of placket toward main detail on «button stand edge» line and sew neckline edge from button stand edge to mark. Snip seam allowance of neckline near the mark, turn button stand wrong side out, press. Make buttonholes on inner placket. Left front: Pin button front band facing, right sides together to left front and sew center front edge and the neckline to mark. Snip neckline seam allowance near the mark, turn front band facing onto wrong side, press.
3. Sew sides to fronts, serge and press seam allowances toward center.
4. Sew yoke to upper front, serge and press seam onto yoke.
5. Make and fasten pleats on sleeve. Sew sleeve to upper back, serge and press seam onto sleeve.
6. Make and fasten pleats on upper back. Sew back and sleeve to front and yoke, trimming front in corner. Clip into curves, serge and press.
7. Pin stand-up collar, right sides together, and sew outer edges. Trim corners and clip into curves. Turn stand-up collar right side out, straighten, press.
8. Pin right and left front band facing to the right side, insert stand-up collar between main garment and right and left facings and sew from mark to shoulder seam. Trim inner stand-up collar edge near shoulder seams and sew outer stand-up collar into neckline. Then from shoulder seam to marker, sew together with front band facing. Clip into curves, turn facings onto wrong side. Turn seam allowance of inner stand-up collar inside, and topstitch into connecting seam.
9. Pin right front over left front, matching center lines, and baste together. Sew upper front to lower front, serge and press seam downwards. Sew upper back to lower back, serge and press seam allowances upwards.
10. Sew side and sleeve seam with one continuous stitch. Serge and press seam toward back.
11. Sew cuff into ring, press seam apart. Press cuff in half lengthwise, wrong sides together. Pin cuff onto wrong side of sleeve and stitch. Serge seam allowances, turn cuff right side out.
12. Serge lower edge of garment, press hem allowance onto wrong side, and topstitch.
13. Sew buttons on left front.
14. Fold belt in half lengthwise, right sides together, and sew outer edges, leaving an opening for turning right side out. Trim corners, turn belt right side out. Sew the opening closed.

TECHNICAL DRAWING:

