

## Sewing Pattern — Sweatshirt 4385

Recommendations on fabric: dense knit fabric.

You will also need: fusible interfacing, zipper (length is shown on front pattern piece), lining for pocket sackings.

If the pattern has double contour the seam allowances are included.

If the pattern has single contour, the seam allowances are NOT included and need to be added when laying out and cutting details.

Seam allowance: all seams 1 cm

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to take into account pieces to be duplicated or cut on a fold.



When sewing the garment, pay attention to notches, they must coincide.

### **CUTTING:**

(On the pattern pieces, “beam” means straight of grain. Lay out your pieces accordingly. Some pieces will be cut on the fold. This is noted on the pattern piece. Mark all notches and other design features such as darts, pleats etc. from the pattern onto your fabric.)

#### Main fabric:

1. Back – cut 1 on fold
2. Front – cut 2
3. Cuff – cut 2
4. Hood — cut
5. Lower placket – cut 1
6. Off-set welt – cut 2

#### Lining:

1. Big pocket sacking – cut 2
2. Small pocket sacking – cut 2

### **Advice:**

Knit fabric pieces are sewn together with special stretch-stitch or narrow zig-zag stitch. Seam allowance on hem is stitched with twin needles to save stretchiness. Pieces can also be sewn together with 3 or 4 – thread serger. When serging, cut seam allowances to 0.6 – 0.8 cm.

### **INSTRUCTIONS:**

1. Apply fusible interfacing to off-set welts. Mark pocket location. Apply interfacing to pocket opening. Press off-set welt in half lengthwise wrong side together. Topstitch small pocket sacking onto inner side of off-set welt.

Sew off-set welt to front on lower line of pocket marking. Sew big pocket sacking to front on upper line of pocket marking. End stitches near short marking lines. Cut pocket opening through. At 1-1.5 cm from the ends of pocket make slanting cuts (dog's tail). Turn off-set welt and big pocket sacking wrong side out through the given slit. Fasten ends of pocket from the wrong side with double back-stitch. Sew and serge edges of sackings.

2. Sew shoulder edges. Sew side edges together with sleeve seam. Press seams to back and serge.

3. Sew cuff into ring. Fold cuff in half lengthwise right side out and press. Sew cuff to sleeve, easing in sleeve.

4. Sew hoods, serge seam allowances. Turn outer edge twice inside at 1 cm and topstitch. Sew hood into neckline, serge seam allowances.

5. Serge front band edges. Serge one long edge of placket. Sew unserged edge of placket to sweatshirt, slightly stretching the placket. Sew in zipper. Bend zipper with placket and topstitch into zipper connecting seam. Turn placket inside and topstitch into upper edge connecting seam.

### **TECHNICAL DRAWING:**

