

Sewing Pattern — Skirt 4118

Recommendations on fabric: fabric suitable for dresses.

You will also need: fusing; invisible zipper.

Seam allowances are provided if the pattern has double contour.

Seam allowances are NOT included if the pattern has single contour and need to be added when laying out and cutting details.

Seam allowance 1 cm on all edges, 2 cm on hem.

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count double and symmetrical details.

When sewing the garment, pay attention to notches, they must coincide.

CUTTING:

Main fabric:

1. Yoke – 2 details
2. Right side part – 2 details
3. Central part – 2 details
4. Left side part – 2 details
5. Facing of left front part – 2 details
6. Lower part – 2 details
7. Top facing – 2 details

Fusing:

1. Facing of left front part – 2 details
2. Top facing – 2 details

INSTRUCTIONS:

1. Apply fusing to facings.
2. Process back part. Stitch right side part to central part, press seam allowances towards center and serge. Stitch loosely along top edge of central parts and gather ruffles. Stitch yoke to the skirt, press seam allowances upwards and serge.
3. Put together the facing of left front part and left side part and overstitch lower edge. Turn the facing onto wrong side, press. Stitch loosely along top edge lower part/s and gather ruffles. Put together lower part and facing of left front part right sides together and sew. Press the seam upwards and serge. Topstitch the facing onto the skirt along marked line.
4. Sew left side part with the skirt parts, press seam allowances towards center and serge.
5. Front part is processed in the same way.
6. Serge separately left side edges. Sew left side edge from zipper marker up to hem, press seam allowances apart. Sew in zipper. Sew right side edge. Press the seam to back part and serge.
7. Sew right side edge of the top facing, press seam allowances apart. Serge lower edge. Put together the facing and skirt right sides together and overstitch upper edge. Topstitch seam allowances on the facing by 0.2 cm off the seam. Turn facing onto wrong side, press. Turn inside open edges of facing and sew to zipper band.
8. Serge the seam allowance of the hem of the garment, press onto wrong side and topstitch.



TECHNICAL DRAWING:

