

Sewing Pattern — Dress 4117

Recommendations on fabric: natural or mixed knitted fabric of 3 colors

If the pattern has double contour the seam allowances are included.

Seam allowances are NOT included by default and need to be added when laying out and cutting details if your pattern has single contour.

Seam allowance: along the edge of the dress - 2 cm; on armhole - 1.5 cm; all other seams - 1 cm

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



CUTTING:

Fabric 1:

1. Front part 1 – 1 detail
2. Front part 4 - 1 detail

Fabric 2:

1. Front part 2 – 1 detail
2. Front part 5 – 1 detail

Fabric 3:

1. Front part 3 – 1 detail
2. Right back part – 1 detail
3. Left back part – 1 detail
4. Neckline facing – 1 detail

Advice:

Knitted fabric details are sewn together with special elastic or narrow zig-zag stitch. When serging cut seam allowances to 0.6 – 0.8 cm. Seam allowance on turnup is stitched with twin needles to save stretchiness. Details also can be sewn together via 3 or 4 – threaded serger.

INSTRUCTIONS:

1. Mark and sew dart on front part.
1. Cut depth with serger.
2. Sew all relieve edges of front part. Serge.
3. Sew middle edge of back part. Serge.
4. Sew side seams and shoulder edge.
5. Serge edge of the armhole, turn inside and topstitch.
6. Fold the facing in half lengthwise and overstitch ends, exactly up to markers (from one and another sides). Slash seam allowances and stitch to neckline of back part and of front part.
7. Serge lower edge of the dress. Turn seam allowance inside and topstitch. Make a bow.

TECHNICAL DRAWING:

