

Sewing Pattern — Dress 4110

Recommendations on fabric: two side silk fabric suitable for dresses.

You will also need: invisible zipper, fusing, 2 hooks and 2 eyes.

Seam allowances are included if the pattern has double contour.

Seam allowances are NOT included if your pattern has single contour and need to be added when laying out and cutting details. All seams 1 cm. Hem of the garment 3 cm.

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.

Notes on patterns are written on the right side.

CUTTING:

Main fabric:

1. Left top part of front part - 1 detail
2. Right top part of front part - 1 detail
3. Side front part - 2 details
4. Side back part - 2 details
5. Central back part - 1 detail
6. Back part of the skirt – 1 detail
7. Front part of the skirt – 1 detail
8. Fly-piece on skirt – 1 detail
9. Left part of collar - 2 details
10. Right part of collar - 2 details
11. Belt – 1 detail

Fusing:

1. Left part of collar - 1 detail
2. Right part of collar - 1 detail



INSTRUCTIONS:

1. Apply fusing to details of collar.
2. Sew relieve seams on back part, press seam allowances towards center and serge. Sew relieve edges of front part, press seam allowances towards center and serge.
3. Sew shoulder seams, press seam onto back part and serge.
4. Put together details of right part of collar right sides together and overstitch outer edge and middle edge up to marker. Slash seam allowances in corners, slash on rounded parts. Put together details of left collar right sides together and overstitch outer edge and middle edge up to marker. Slash seam allowances in corners, slash on rounded parts. Put together left and right collars right sides together and sew open parts of middle edge. Press apart the seam, turn collar onto right side, straighten and press.
5. Put collar onto wrong side of top parts of the dress and stitch along the edge of neckline. Press seam allowances, slash, serge. Turn collar onto right side. Fix open edge of left part of collar to the edge of left front part, forming a stand-up collar 1 cm high and serge. Put right front part onto left front part, turn right part of collar, and topstitch, leveling details along waistline. Fix open edge of right collar to lower edge of front part, making small plaits.
6. Sew darts on parts of the skirt, press depths towards center. Serge seam allowance of outer edge of flypiece part, press onto wrong side and topstitch. Make and fasten plaits according to markers along the top edge. Put outer flypiece part onto front part and fix along side and top edges (outer flypiece part is shorter than the front part by the seam allowance on hem).
7. Stitch back and front part of the skirt to top parts of back part and of front part. Press the seam upwards and serge.
8. Cut or take a ready bias tape 4 cm wide for oversteitching armhole. Fold bias tape in half lengthwise wrong sides together and press. Put the bias tape onto edge of the armhole from the right sides and oversteitch, turn the bias tape onto wrong side and topstitch along the fold onto main detail.
9. Serge left side edges separately on back part and top part. Sew left side edges from armhole to top marker and from lower marker downwards, press seam allowances apart, pressing slit for zipper. Sew in zipper. Sew right side edges, press seam onto back part, serge.
10. Serge hem of garment. Turn onto wrong side, press and undersew with invisible stitches.
11. Fold belt in half lengthwise right sides together and oversteitch along contour, leaving slit for turning it out, and inserting hooks and eyes into short sides. Slash seam allowances in corners. Turn the belt inside out, straighten corners and press. Sew the slit.
12. Cut a bias tape for rose, 90 cm long and 12 cm wide. Fold it in half lengthwise wrong sides together, serge edges. Stitch loosely along the edges and gather ruffles. Form a flower and fix it on the belt.

TECHNICAL DRAWING:

