

## Sewing Pattern — Vest 4492

Recommendations on fabric: natural or mixed suiting fabric, contrast fabric.

You will also need: fusible interfacing, 4 buttons, lining, trim band.

If the pattern has a double line around it, the seam allowances are included.

**Note:** By default, seam allowances are NOT included (single line) and will need to be added when laying out and cutting details.

Seam allowance: all seams – 1 cm

Attention! First of all, please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to take into account pieces to be duplicated or cut on a fold.

When sewing the garment, pay attention to notches, they must match up with corresponding pieces.



### **CUTTING:**

#### Main fabric:

1. Center back - cut 2
2. Side back — cut 2
3. Central front — cut 2
4. Side front – cut 2
5. Back neck facing – cut 2
6. Back lower edge facing – cut 2
7. Side back facing – cut 2
8. Front facing – cut 2
9. Welt – cut 2

#### Lining:

1. Center back – cut 2
2. Side back – cut 2
3. Side front – cut 2

Fusible interfacing: front facing, back neck facing, front neck facing, welts.

### **INSTRUCTIONS:**

1. Apply fusible interfacing to listed pieces.

2. Sew side and center fronts, inserting trim band. Press darts toward center.
3. Sew center back seam. Press seam to the left. Sew side and center backs, inserting trim band. Press seams toward center.
4. Sew shoulder and side seams. Press seams to back.
5. Sew shoulder edges of neck facing. Press apart seams. Sew facing to neck, inserting trim band. Clip on curves and press.
6. Fold welt in half lengthwise wrong side out and stitch on short edges. Trim corners and turn right side out. Serge lower edge. Place welt onto front leveling connection line with lower marking line (welt fold is directed to lower edge) and topstitch. Fold welt upwards and topstitch on two short sides.
7. Sew center and side backs from lining. Sew center edge. Sew inner facing to back lining. Sew lower facings to lining details. Press seam allowances upwards. Sew lining details the same way as main fabric details, leaving an opening in left side seam. Place lining and garment right sides together and stitch on front band, neckline and lower edge. Clip on curves. Topstitch neck edge allowance onto lining at 0.2 cm from the edge.
8. Stitch armhole through the opening in side seam in two steps: Back armhole from shoulder seam to side seam and front armhole from shoulder seam to side seam. Sew the opening closed.
9. Serge buttonholes on right front, sew on buttons on left front.

**TECHNICAL DRAWING:**

