

## Sewing Pattern — Dress 4495

Recommendations on fabric: natural or mixed dress fabric with lycra, guipure with lycra.

You will also need: invisible zipper, fusible interfacing.

If the pattern has a double line around it, the seam allowances are included.

**Note:** By default, seam allowances are NOT included (single line) and will need to be added when laying out and cutting details.

Seam allowance: hem – 2 cm, hem of sleeves and lower edge of peplum – 0 cm, other seams – 1 cm

Attention! First of all, please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to take into account pieces to be duplicated or cut on a fold.

When sewing the garment, pay attention to notches, they must match up with corresponding pieces.



### **CUTTING:**

#### Main fabric:

1. Lower back - cut 2
2. Lower front — cut 1
3. Waistband — cut 1
4. Collar – cut 1
5. Bow – cut 1

#### Guipure:

1. Upper back – cut 2
2. Upper front – cut 1
3. Back peplum – cut 2
4. Front peplum – cut 1
5. Sleeve – cut 2

#### Fusible interfacing:

1. Collar – cut 1
2. Waistband – cut 1

Lining: upper front and upper back. Pieces are cut from main fabric.

Note: Lower edges of sleeves and peplums are not serged. Cut pieces should place at the edge of cloth.

### **INSTRUCTIONS:**

1. Apply fusible interfacing to listed pieces.
2. Sew darts on backs. Press darts toward center. Sew darts on fronts. Press darts toward center. Sew darts on peplums. Press darts toward center of back and front.
3. Sew shoulder and side edges on tops. Press apart seams. Sew side edges of peplums. Serge seams and press onto back. Sew side edges of lower parts. Serge seams and press onto back.
4. Fold collar in half lengthwise and stitch ends. Trim corners and turn out.
5. Sew darts on lining pieces. Cut darts off and press toward center. Sew side and shoulder edges. Press apart seams. Overstitch neck with lining inserting collar between main fabric and lining. Clip on curves, fold lining inside. Pin main fabric and lining on lower edge and armhole edge. Then sew as one detail.
6. Sew upper and lower parts of the dress, inserting the peplum. Serge seam allowances and press it upwards.
7. Fold belt in half lengthwise wrong side out and stitch on long edge. Turn belt right side out. Press belt, placing the seam in the center of belt. Place belt onto dress covering waist seam. Fasten ends of belt to back center seam.
8. Serge back center edges separately. Sew center seam from zipper mark down. Press apart seam. Sew in zipper.
9. Sew sleeve edge. Serge seam and press onto back part. Sew in sleeves matching marks. Serge seams.
10. Fold bow detail wrong side out and stitch on three sides, leaving an opening. Trim corners, turn bow out and press. Sew the opening closed (by hand). Cut a strap 6x6 cm. Stitch on one side and turn out. Sew bow into strap and tack to dress according to technical drawing.
11. Serge hem of dress. Fold to wrong side, press and slipstitch.

### **TECHNICAL DRAWING:**

