

Sewing Pattern —Tunic 4499

Recommendations on fabric: natural or mixed shirting fabric.

You will also need: invisible fusible interfacing, 2 buttons.

Seam allowances: all seams - 1 cm, hem of dress – 1.5 cm, hem of sleeve – 2 cm.

Note on seam allowances:

- If the pattern has double contour the seam allowances are included. They are 1 cm unless specified otherwise.
- If the pattern has single contour, the seam allowances are NOT included and need to be added when laying out the pattern.

Note on length of fabric:

Attention! The amount of fabric needed for your pattern is not included. It will depend on the selected pattern size, the width, and design of the fabric you plan to use. First, print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm). Measure how much fabric you will need. Don't forget to account for pieces that need to be cut multiple times and pieces that are cut on the fold.



CUTTING:

Main fabric:

1. Back yoke – cut 1
2. Back – cut 2
3. Front – cut 1
4. Placket – cut 2
5. Sleeve – cut 2
6. Stand collar – cut 2
7. Sleeve stripe – cut 2

Fusible interfacing:

1. Placket – cut 1
2. Outer collar – cut 1

INSTRUCTIONS:

1. Apply fusible interfacing to listed pieces.
2. Sew center back seam, press seams to the left and serge. Sew yoke to back, press seam upwards and serge.
3. Sew darts on front, press them upwards.

4. Press plackets in half lengthwise right side out. Sew plackets to front on long edges, leaving 1 cm to lower edge. Trim seam allowance of front in corners, leaving 1mm to the stitch. Put ends of plackets inside and sew, fastening lower edge.
5. Sew shoulder edges, press seams to back and serge.
6. Place stand collars right sides together and stitch outer edge, starting and ending stitch exactly at the collar connecting line. Turn collar right side out and press.
7. Sew outer collar into neckline, turn inside open edge of inner collar and topstitch into connecting seam.
8. Fold sleeve stripe wrong side out and stitch long and short sides. Cut seams in corners, turn detail right side out and press. Serge a buttonhole. Sew stripe from wrong side of sleeve according to marking. Sew a button from the right side.
9. Sew sleeves into open armholes. Serge seams. Sew sleeve seam and side seam in one step. Press seams to back and serge.
10. Serge hem, turn to wrong side, press and topstitch. Turn hem of sleeve twice at 1 cm and topstitch.

TECHNICAL DRAWING:

