

Sewing Pattern — Skirt 4103

Recommendations on fabric: denim.

You will also need: fusing; 1 zipper; 2 zippers for pockets; 1 button, cotton fabric for pocket bags.

If the pattern has double contour the seam allowances are included.

Seam allowances are NOT included by default and need to be added when laying out and cutting details if your pattern has single contour.

Seam allowance: all seams -1 cm, along slit — 3 cm, hem of the garment - 4 cm

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



CUTTING:

Main fabric:

1. Central back part – 2 details
2. Side back part – 2 details
3. Back yoke – 4 details
4. Central front part – 2 details
5. Side front part – 2 details
6. Front yoke – 4 details
7. Button catch — 1 detail
8. Bigger pocket bag — 2 details

Cotton fabric:

1. Smaller pocket bag — 2 details

INSTRUCTIONS:

1. Apply fusing to pocket opening. Cut pocket opening in the center along marking line, making cross slashes to pocket marker corners. Press seam allowances onto wrong side. Put zipper under pocket opening. Stitch zipper from right side of front part at 0. 1 cm off the pocket opening. Stitch smaller pocket bag to lower tape of zipper and turn downwards. Stitch bigger pocket bag to top tape of zipper. Sew edges of pocket bags.
2. Sew side and central front parts. Slash seam in corner, press seam allowances towards side central part and serge. Put decorative stitch at 0. 5 cm off the seam.

3. Stitch yoke to front part. Press seam onto yoke, serge and stitch on.
4. Sew details of central and side back parts. Press seam towards center of back part, serge and put decorative stitch on 0.5 cm off the seam. Stitch yoke of back part. Press seam onto yoke, serge and stitch on.
5. Sew side seams. Serge and press to back part.
6. Sew side seams of inner of yokes. Press seams apart. Serge lower edge of yokes.
7. Cut one-piece facing off the left front half, leaving seam allowance along middle seam of 1 cm. Cut off one-piece facing on the left inner yoke, cut off the section equal to the length of one-piece fly-piece on right inner yoke. Sew middle edge of front halves, starting the stitch near one-piece facing edge. Serge front middle edge from stitch beginning up to hem. Serge edge of the fly-piece separately. Press one-piece fly-piece onto wrong side. Level zipper to middle edge of left half and stitch. Stitch free tape of zipper to one-piece fly-piece of right half. Stitch inner yoke to fly-piece. Fold button catch in half lengthwise wrong sides together and sew longitudinal and short lower edges. Serge open edges of button catch. Stitch button catch to zipper connecting seam to left half. Fold outer and inner yokes between themselves and overstretch upper edge and corner on back part up to marked line of middle edge of back part. Put decorative stitch along marked line on right half. Make barred end at the end of zipper from right side of the skirt. Stitch open edge of left inner yoke to zipper connecting seam. Join lower ends of fly-piece and button catch from wrong side. Topstitch inner yokes into top yokes connecting seam.
8. Insert right part of back part into left part between inner yoke and main detail. Sew middle edge of back part from corner up to the slit. Serge, press to left side, turn details out.
9. Serge seam allowances along slit. Slash middle seam of back part, press slit apart. Press seam allowance of hem first at 1 cm, then again at 3 cm over the slit upper seam allowance. Put decorative stitch along middle edge of back part, slit and hem of the skirt according to technical drawing.
10. Make buttonhole as marked and sew a button.

TECHNICAL DRAWING:

