

## Sewing Pattern — Skirt 5427

Recommendations on fabric: velour or other appropriate apparel fabric.

You will also need: 1 zipper and fusible interfacing

If the pattern has double contour the seam allowances are included.

Seam allowances are NOT included by default and need to be added when laying out and cutting details if your pattern has single contour.

Seam allowance: 1cm for all seams unless otherwise specified.

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



### **CUTTING:**

(On the pattern pieces, "beam" means straight of grain. Lay out your pieces accordingly. Some pieces will be cut on the fold. This is noted on the pattern piece. Mark all notches and other design features such as pleats etc. from the pattern onto your fabric.)

#### Fabric:

1. Gore – cut 6
2. Facing – cut 2 of fabric and 2 of interfacing

Interfacing: front band, top collar and collar stand.

### **INSTRUCTIONS:**

1. Apply the interfacing to the wrong side of the facings.
2. Sew all gore sections together-- excluding place for zipper in the left side seam.
3. Press seams open.
4. Sew the facings together end to end across right side. Press the seam open. Sew facing to the top edge of the skirt, right sides together. Trim and press the seam up toward the facing.
5. Insert the zipper. With the top of zipper teeth just at the seam line and the top of the zipper tapes extended into the facing.

6. Fold the facing toward the inside of skirt along seamline. The top of the zipper tape will fold neatly inside with the facing.
7. Topstitch the skirt edge to the facing. Fold the facing left side edges under and slipstitch them to the zipper tape.
8. Fold the hem under and topstitch or hem as desired.

**TECHNICAL DRAWING:**

