

Sewing Pattern — Hoodie 4097

Recommendations on fabric: knit fabric of middle stretchiness of natural or mixed fibers

You will also need: 5 buttons

If the pattern has double contour the seam allowances are included.

Seam allowances are NOT included by default and need to be added when laying out and cutting details if your pattern has single contour.

Seam allowance: 1 cm on all edges .

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



CUTTING:

(On the pattern pieces, “beam” means straight of grain. Lay out your pieces accordingly. Some pieces will be cut on the fold. This is noted on the pattern piece. Mark all notches and other design features such as darts, pleats etc. from the pattern onto your fabric.)

Fabric:

1. Front – cut 1
2. Side – cut 1 on fold
3. Back – cut 2
4. Waistband – cut 1
5. Right hood – cut 1
6. Left hood – cut 1
7. Left hood facing - cut 1
8. Right hood facing – cut 1
9. Sleeve – cut 2
10. Cuff – cut 2

Advice:

Knitted fabric details are sewn together with special elastic or narrow zig-zag stitch, and seams can be finished or serged with a serger. When serging, cut seam allowances to 0.6 – 0.8 cm. Seam allowance on turnup is stitched with twin needles to save stretchiness.

INSTRUCTIONS:

1. Sew middle seam of backs. Serge and press toward left.
2. Place pockets on front, right sides together and sew from hem up to mark. Turn right side out.
3. Sew side to front from top up to pocket opening. Serge and press onto front. Sew top edges of pocket. Serge.
3. Cut seam allowance of closure on left sleeve and stitch to front. Serge. Serge lower edges of closure on right sleeve and front. Stitch right sleeve to front, finishing the stitch near closure. Serge. Sew sleeves into armhole of back. Serge.
4. Sew side seams and sleeve seams as one. Serge.
5. Fold cuff in half lengthwise. Sew sections 1, 2 and 3, leaving two slits. Press open seam allowance. Sew cuff into ring and fold in half. Turn slit seam allowances inside and slip-stitch openings by hand. Stitch cuff to sleeve matching marks with sleeve seam. Slit for finger should be towards front side. Serge.
6. Sew seams of the hood facing. Press the seam open. Serge outer edge of the facings. Sew the hood into the neckline. Put the facing on hood and sew front vertical seam. Press the seam apart. Press closure seam allowances on front part and sleeve onto wrong side. Turn the facing onto right side and topstitch edge of the hood. Sew lower edge of facing into the neckline and serge neckline edge. Topstitch front and left hood, fixing seam allowance of closure at the same time. Topstitch sleeve and right hood, fixing seam allowance of closure at the same time.
7. Sew waistband into ring. Fold in half lengthwise and while slightly stretching to fit, sew to bottom edge of hoddie. Serge.
8. Make buttonholes on front part and left hood, sew buttons on right part.

TECHNICAL DRAWING:

