

PATTERN OVERVIEW

Made-to-measure pattern:

The pattern is drafted by our proprietary software specifically for your measurements that you supply when making an online order. We strongly recommend that you request a free preview to check the style lines and the amount of fabric needed before ordering the paid version.

Pattern features:

Pencil skirt with back wrap, zipper in center back seam. The skirt sits at natural waistline, the length is at center of kneecap, ease around waist is approx. 1", ease around hips approx. 1.5" depending on the size.

Recommendations on fabric: wool or semi-wool, dress fabric, suiting fabric, bottom weight woven fabric.

You will also need: fusible interfacing, 1 zipper (the length in cm and inches is mentioned on the pattern piece).

Seam allowances:

If the pattern has double contour the seam allowances are included and are as follows: 1/2 inch on all edges, 5/8 inch on center back seam for zipper installation, hem of skirt – 1.5 inch.

Attention! Seam allowances are NOT included by default and need to be added when laying out and cutting details if your pattern has single contour.

Fabric requirements:

To estimate fabric requirements, get a free preview for the pattern in your size at www.Lekala.net and use [Online Fabric Estimator](#).

Alternatively you may print all the paper patterns and lay them out at the width of fabric you plan to use (usually 44 inches to 60 inches) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must match up.



CUTTING:

Lay pattern pieces out using the straight of grain line. Some pieces may be cut on the fold. This is noted on the pattern piece. Mark all notches and other design features such as darts, pleats etc. from the pattern onto your fabric.

Main fabric:

1. Side front - cut 2
2. Center front - cut 1 on fold
3. Side back - cut 2
4. Center back - cut 2
5. Back hem facing - cut 2
6. Front facing - cut 1 on fold
7. Back facing - cut 2


Fusible interfacing:

1. Back hem facing - cut 2
2. Front facing - cut 1 on fold
3. Back facing - cut 2

INSTRUCTIONS:

1. Apply fusible interfacing to back hem facings. Serge inner edge of hem facing. Sew front skirt and hem facing right sides together. Turn facing to inside. Straighten seam and corner. Fasten facing to skirt (either use double-sided fusible interfacing, or slipstich, or make decorative stitch along front edge).
2. Sew side fronts to center front. Serge and press seams towards center.
3. Serge separately center back edges of center back pieces. Sew center back seam from zipper mark down to lower edge. Press seam open, pressing slit for zipper.
4. Install zipper.
5. Sew side backs to center back. Serge and press seams towards center.
6. Overlap lower parts of side backs. Pin and sew them to lower edge of center back. Serge and press seam upwards.
7. Sew side seams. Serge and press seams towards back.
8. Apply fusible interfacing to facings.
9. Sew side seams of facings. Press seams open. Serge lower edge of facing. Pin facing to skirt right sides together and sew. Turn facing to inside and topstitch. Tack facing to side seams and zipper tape.
10. Serge lower edge of front skirt, turn under, press, and slipstitch.

TECHNICAL DRAWING:



*If you have any further questions regarding the pattern,
please don't hesitate to contact us at info@sewist.com.
We are always happy to help!*
