

Sewing Pattern — Blouse 4096

Recommendations on fabric: knit fabric of middle stretchiness of natural or mixed fibers

If the pattern has double contour the seam allowances are included.

If the pattern has single contour, the seam allowances are NOT included and need to be added when laying out and cutting details.

SEAM ALLOWANCE: on hem and sleeve hem—

1. 5 cm; on front part wrap —

1. 5 cm; all other seams - 0.7 cm.



Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.

CUTTING:

Fabric:

1. Back part — 1 detail
2. Front part – 2 details
3. Sleeve – 2 details
4. Collar – 1 detail
5. Cuff – 2 details

ATTENTION: Before sewing check your head goes through sewn neckline.

Advice:

Knitted fabric details are sewn together with special elastic or narrow zig-zag stitch. When serging cut seam allowances to 0.6 – 0.8 cm. Seam allowance on turnup is stitched with twin needles to save stretchiness. Details also can be sewn together via 3 or 4 – threaded serger.

INSTRUCTIONS:

1. Sew darts on sleeve details. Cut the depth with serger up to 0.7 cm.
2. Serge wrap edge of front part, press onto wrong side and topstitch. Put right front part on left and fix along side edge.
3. Stitch back parts of sleeves to back part. Stitch front parts of sleeves to front part. Press seam allowances on sleeve and serge.
4. Sew lower edge of sleeve and side edge with one seam, press seam onto back part and serge.
5. Stitch loosely along neckline of front part and gather ruffles.

6. Fold collar in half lengthwise right sides together and sew section between «o» marks. Slash seam allowances near mark, turn collar the right side out. Sew collar into ring. Turn collar out and press. Fold collar in half, wrong sides together. Sew collar in the neckline, aligning notches and stretching edge of collar. Seam of collar is near left shoulder dart of sleeve. Press collar connecting seam sewing.
7. Sew cuff into ring, turn and press. Fold cuff in half, wrong sides together. Stitch along the lower edge of sleeve loosely and gather ruffles to the length of cuff. Stitch cuff to lower edge of sleeve, press seam allowances.
8. Serge hem of garment, press onto wrong side and topstitch.

TECHNICAL DRAWING:

