

Sewing Pattern — Tunic 4093

Recommendations on fabric: natural / mixed, medium to high stretch-knit fabric

If the pattern has a double line around it, the seam allowances are included.

Note: By default, seam allowances are NOT included (single line) and will need to be added when laying out and cutting details.

Seam allowance: on hem and edge of sleeve –1.5 cm, all other seams 0.7 cm

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need.

Don't forget to take into account pieces to be duplicated or cut on a fold.

When sewing the garment, pay attention to notches, they must match up with corresponding pieces.



CUTTING:

(On the pattern pieces, “beam” means straight of grain. Lay out your pieces accordingly. Some pieces will be cut on the fold. This is noted on the pattern piece. Mark all notches and other design features such as darts, pleats etc. from the pattern onto your fabric.)

Darts: The fold of the dart is always pressed toward the center of your garment, or down toward the hem.

Advice:

Knit fabric pieces are sewn together with special stretch-stitch or narrow zig-zag stitch. Seam allowance on hem is stitched with twin needles to save stretchiness. Pieces can also be sewn together with 3 or 4 – thread serger. When serging, cut seam allowances to 0.6 – 0.8 cm.

Main fabric:

1. Back – cut 1 on fold
2. Front — cut 1 on fold
3. Sleeve – cut 2
4. Collar – cut 1

INSTRUCTIONS:

1. Sew darts on front, press towards hem.
2. Make soft pleats along front neckline according to markers. Depths are pressed towards side edge. Baste in place.
3. Sew shoulder seams. Serge and press seams toward back.
4. Sew collar into ring, press seam allowances open. Sew inner edge of collar into the neckline, matching notches and stretching edge of collar. Seam of collar is near left shoulder seam. Press collar connecting seam.
5. Sew sleeve into open armhole, matching notches. Serge and press seam allowances.
6. Sew side seam, stitching sleeve seam at the same time. Serge and press seam allowances toward back.
7. Serge bottom edge of garment, lower edge of sleeve, and outer edge of collar. Turn onto wrong side, press, and topstitch.

TECHNICAL DRAWING: