

Sewing Pattern — Blouse 4090

Recommendations on fabric: blouse fabric of natural or mixed fibers.

You will also need: fusing, 9 buttons.

If the pattern has double contour the seam allowances are included.

Seam allowances are NOT included by default and need to be added when laying out and cutting details if your pattern has single contour.

Seam allowance: on hem of the garment – 1.5 cm, all other seams – 1cm .

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



CUTTING:

Main fabric:

1. Upper front part - 2 details
2. Lower central front part - 2 details
3. Lower side front part - 2 details
4. Back part - 1 detail
5. Back part sidebody – 2 details
6. Sleeve – 2 details
7. Collar – 1 detail
8. Cuff – 2 details
9. Front neckline facing – 2 details

Fusing:

1. One-piece panel – 2 details
2. Front neckline facing – 2 details
3. Cuff – 2 details

INSTRUCTIONS:

1. Apply fusing to one-piece panels, neckline facings and cuff.
2. Sew darts on back part. Press darts towards center. Sew relieve seams on back part. Serge and press the seam towards center.
3. Sew details of lower front part. Serge and press towards center of front part.
4. Stitch loosely on lower edge of top front part between notches and gather ruffles. Sew top and

bottom front part. Serge and press downwards.

5. Serge outer edge of front part neckline facing. Stitch the facing to one-piece panel, press seam allowance onto panel. Turn panel and facing onto right side and overstretch the neckline up to marker. Slash neckline at marker level. Slash seam allowance on rounded parts. Turn facing onto wrong side and press. Turn seam allowance of the panel and topstitch.

6. Sew shoulder and side edges. Serge seams and press to back part.

7. Fold collar lengthwise right sides together and overstretch from end marker up to the fold. Slash seam allowance of collar near end marker. Cut seam allowances in corners and turn onto right side. Sew outer edge into the neckline. Turn seam allowance of inner edge inside and topstitch into outer edge connecting seam.

8. Serge side edges of sleeve. Sew edge of sleeve up to marker. Press apart the seam. Stitch loosely along rounding between notches and along the lower edge of sleeve and gather ruffles. Sew sleeve into armhole. Serge and press to the sleeve. Fold cuff lengthwise right sides together, sew edges and section up to notches. Slash seam allowance near marker. Start and finish the stitches exactly near marked line. Cut seam allowances and turn onto right side. Stitch outer edge to the sleeve. Turn inner edge inside and topstitch into outer edge connecting seam.

9. Serge hem of the garment, press onto wrong side and topstitch.

10. Serge buttonholes on right front part, sew buttons on left front part. Serge buttonholes on cuffs and sew buttons.

TECHNICAL DRAWING:

