
Sewing Pattern — Blouse 4087

Recommendations on fabric: Knitted fabric of medium or high stretchiness of natural or mixed fibers

Seam allowances are provided if the pattern has double contour.
Seam allowances are NOT included if the pattern has single contour and need to be added when laying out and cutting details. 1 cm for all seams, 2 cm for garment hem and sleeve hems, 1.5 cm for front neckline and front middle seam.

Seam allowance : seam allowance on edge neckline and armhole – 1.5 cm, all other seams - 1 cm.

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count double and symmetrical details.

When sewing the garment, pay attention to notches, they must coincide.

CUTTING:

Main fabric:

1. Front part – 1 folded detail
2. Back part – 1 folded detail
3. Lower part – 1 folded detail

Advice: Knitted fabric parts are sewn together with a special elastic or narrow zigzag stitch. Seam allowance on hem is stitched with a double needle or on coverstitch machine to save stretchiness. It is also possible to stitch details together on 3- or 4- needled serger.



INSTRUCTIONS:

1. Sew side and shoulder edges. Serge and press towards back part.
2. Serge neckline edge, turn onto wrong side and topstitch.
3. Serge edge of the armhole, turn onto wrong side and topstitch.
4. Sew seam of lower part. Serge. Fold lower part in half lengthwise and stitch, stretching it slightly. Seam is near left side seam. Serge and press downwards.

TECHNICAL DRAWING: