

## Sewing Pattern — Skirt 4285

Recommendations on fabric: natural / mixed thin costume fabric.

You will also need: fusing, zipper.

If the pattern has double contour the seam allowances are included.

If the pattern has single contour, the seam allowances are NOT included and need to be added when laying out and cutting details.

Seam allowance: all seams - 1 cm, hem of the garment – 4 cm

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



### **CUTTING:**

Main fabric:

1. Central part of the back – 2 details
2. Middle part of the back – 2 details
3. Side part of the back – 2 details
4. Front – 1 detail
5. Back yoke – 4 details
6. Front yoke – 2 details

Fusing:

1. Back yoke – 2 details
2. Front yoke – 1 detail

### **INSTRUCTIONS:**

1. Apply fusing to yokes.
2. Sew relieve/princess seam on central and middle parts of the back together with the vent. Press seam allowances towards center and serge. Put decorative stitch along the seam at 0.7 cm, topstitch seam allowances of the vent onto central part according to technical drawing.
3. Sew relieve/princess seam on middle and side parts of the back together with the vent. Press seam allowances towards center and serge. Put decorative stitch along the seam at 0.7 cm, topstitch seam allowances of the vent onto middle part according to technical drawing.

4. Serge center edges of the back separately on each detail, serging the vent at the same time. Sew center edge from zipper notch up to vent corner and vertical edge of the vent. Press seam allowances apart, pressing the slit for zipper, press apart seam allowances of the vent, making a counter pleat. Topstitch seam allowances of the vent onto the back according to technical drawing. Sew in the zipper.
5. Stitch yoke of the back to back panel, press seam allowances upwards. Put decorative stitch along the seam at 0.7 cm. Stitch yoke of the front to front panel, press seam allowances upwards. Put decorative stitch along the seam at 0.7 cm.
6. Sew side seams, press apart and serge seam allowances.
7. Sew side seams of inner yokes. Serge lower edge. Fold yoke with the skirt right sides together and overstitch upper edge. Topstitch seam allowances onto inner yoke by 0.2 cm off the seam. Turn facings on wrong side, press. Turn inside center edges of inner yoke and sew to zipper tape. Topstitch inner yoke into outer yoke connecting seam.
8. Serge lower edge of the skirt, press onto wrong side and undersew with invisible stitches.

### **TECHNICAL DRAWING:**

