

## Sewing Pattern — Jacket 4084

Recommendations on fabric: natural / mixed suiting fabrics

You will also need: fusible interfacing; lining; shoulder pads; 1 button

If the pattern has a double line around it, the seam allowances are included.

**Note:** By default, seam allowances are NOT included (single line) and will need to be added when laying out and cutting details.

Seam allowance: hem of sleeve - 3.5 cm; all other seams - 1 cm

Attention! First of all, please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to take into account pieces to be duplicated or cut on a fold.

When sewing the garment, pay attention to notches. They must match up with corresponding pieces.



### **CUTTING:**

The word, “beam” used on some patterns means “straight of grain”. Some pieces will be cut on the fold, this is noted on the pattern piece. Mark all notches and other design features such as darts, pleats etc. from the pattern onto your fabric.

Darts: The fold of the dart is always pressed toward the center of your garment, or down toward the hem.

### **Main fabric:**

1. Center back – cut 2
2. Side back – cut 2
3. Side front – cut 2
4. Center front – cut 2
5. Button-stand facing – cut 2
6. Back neck band/facing – cut 2
7. Front neck band/facing – cut 4
8. Lapel – cut 4
9. Upper sleeve – cut 2
10. Lower sleeve – cut 2
11. Lower back facing – cut 1

### **Lining:**

1. Center back – cut 2
2. Side back – cut 2
3. Side front – cut 2
4. Center front – cut 2

5. Upper sleeve – cut 2

6. Lower sleeve – cut 2

\*ATTENTION: lining pieces of back and front are cut excluding the width of lower back facing and button-stand facing.

Fusible interfacing:

1. Button-stand facing – cut 2

2. Back neck facing – cut 1

3. Front neck facing – cut 2

4. Lapel – cut 2

5. Lower back facing – cut 1

**INSTRUCTIONS:**

1. Apply fusible interfacing to listed pieces.

2. Pin lapels right sides together and sew outer edge. Clip into curves, turn lapels right side out, straighten and press. Pin lapels onto center front and baste along neckline edge and central front edge.

3. Sew side fronts to center fronts, clip into curves, press seams apart. Sew side backs to center backs, clip into curves, press seams apart. Sew center back seam, press seam apart. Sew shoulder seams and side seams. Press seams apart.

4. Sew shoulder seams of back neck band and front neck bands, press seams apart. Sew the bands to the neckline, right sides together, clip into curves, press seam toward band.

5. Sew sleeve elbow sleeve, easing in upper part of sleeve and aligning notches. Press seam apart. Sew sleeve seam, press seam apart. Press sleeve hem allowance.

6. Make a gathering stitch along sleeve cap. Sew sleeves into armholes matching notches, and adjusting ease. Sew in shoulder pads.

7. Sew shoulder seams of neck band facings, press seams apart. Sew lower back facing to button-stand facing, press seams apart.

8. Sew lining same as main fabric, leaving a slit in left elbow seam for turning right side out. Sew lining to inner edges of facings. Understitch facing to garment where possible. Sew sleeve lining to sleeve hem. Turn garment right side out through sleeve slit, sew up sleeve slit. Straighten and press.

9. Make buttonhole on right front, sew a button on left front.

**TECHNICAL DRAWING:**

