

## 4695 - Sewing Pattern #4695

Recommendations on fabric: natural/mixed fabrics suitable for outdoor jackets.

You will also need: lining; zipper; elastic tape; decorative cord; 4 buttons.

Seam allowances: all seams 1 cm.

### Note on seam allowances:

- If the pattern has double contour the seam allowances are included. They are 1 cm unless specified otherwise.
- If the pattern has single contour, the seam allowances are NOT included and need to be added when laying out the pattern.

### Note on length of fabric:

*Attention! The amount of fabric needed for your pattern is not included. It will depend on the selected pattern size, the width, and design of the fabric you plan to use. First, print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm). Measure how much fabric you will need. Don't forget to account for pieces that need to be cut multiple times and pieces that are cut on the fold.*



## CUTTING:

### Note on cutting:

*On the pattern pieces, "beam" means straight of grain. Lay out your pieces accordingly. Some pieces will be cut on the fold. This is noted on the pattern piece. Mark all notches and other design features such as pleats etc. from the pattern onto your fabric.*

*When sewing the garment, pay attention to notches, they must match up.*

Main fabric:

1. Upper back – cut 2
2. Upper front – cut 2
3. Lower back — cut 2
4. Lower front – cut 2
5. Back neck facing – cut 1
6. Buttonstand – cut 2
7. Front placket – cut 1

8. Cuff – cut 2
9. Collar – cut 1
10. Pocket – cut 2
11. Flap – cut 4
12. Back hem facing – cut 1
13. Front hem facing – cut 2
14. Sleeve decorative tab - cut 2

Lining:

1. Back lining – cut 2
2. Front lining – cut 2
3. Pocket lining – cut 2

Fusible interfacing:

1. Buttonstand – cut 2
2. Back neck facing – cut 1
3. Flap – cut 4
4. Cuff – cut 2
5. Collar -cut 1

## INSTRUCTIONS:

1. Apply fusible interfacing.
2. Pin together flaps right sides together and sew around all edges. Turn right side out, press. Pin pocket and pocket lining together right sides together and sew pocket opening and upper edge, inserting flap. Fold lining towards wrong side and press. Sew a fixing stitch along pocket opening on flap, with the flap folded towards bottom. Serge the pocket along lower and side edges. Fold seam allowances inside and topstitch pocket.
3. Sew upper back to lower back. Press seam apart. Sew center back seam. Press seam apart.
3. Sew upper front to lower front. Press seam apart.
4. Sew and press apart shoulder and side edges.
5. Make buttonholes on collar. Sew outer collar into neckline. Clip into seam allowances and press apart.
6. Stretch elastic tape, pin and topstitch on the wrong side.
7. Sew shoulder seams of buttonstands and facings. Press seam apart. Sew inner stand collar into neckline. Clip into seam allowances and press apart.
8. Place buttonstand onto front right sides together and sew along the buttonstand edge, inserting zipper, sewing

the collar at the same time. Start and stop stitching exactly at the marked hem line. Stitch along upper edge of collar, making a casing.

9. Sew cuff seam. Press seam apart. Sew outer cuff to sleeve.

10. Sew seams on lining, sew dart, leaving an opening in left side seam. Sew lower facings.

11. Fold front placket in half lengthwise right sides together and sew corners. Turn right side out and press. Sew decorative stitches along outer fold, along upper and lower edges.. Serge inner edge. Pin placket onto front and topstitch along the marked line. Fold placket so that the closure is covered with it, and sew a decorative stitch along placket.

12. Slip stitch together the seam allowances of the seam along neckline and stand collar. Sew lining to buttonstands and facing. Sew lower edge of lining to hem of garment. Sew lining to inner side of cuff. Baste seam allowances on cuff together. Turn right side out through the opening. Sew the opening closed. Thread in the cord. Sew a decorative/fixing stitch along hem of jacket.

13. Fold decorative tab of the sleeve in half lengthwise right sides together and sew along long side and corner. Turn tab right side out, straighten, press. Make buttonhole on tab. Sew decorative tab to sleeve. Sew on button onto sleeve. Sew buttons on flaps.

## TECHNICAL DRAWING:

