

4700 - Sewing Pattern #4700

Recommendations on fabric: natural or mixed soft thin stable fabric suitable for coats.

Seam allowances: all seams 1 cm. Seam allowance along hem, center front, collar fall and hem of sleeve - 0 cm. Seam allowance along upper edge of pocket – 3.5 cm.

Note on seam allowances:

- If the pattern has double contour the seam allowances are included. They are 1 cm unless specified otherwise.
- If the pattern has single contour, the seam allowances are NOT included and need to be added when laying out the pattern.

Note on length of fabric:

Attention! The amount of fabric needed for your pattern is not included. It will depend on the selected pattern size, the width, and design of the fabric you plan to use. First, print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm). Measure how much fabric you will need. Don't forget to account for pieces that need to be cut multiple times and pieces that are cut on the fold.



CUTTING:

Note on cutting:

On the pattern pieces, “beam” means straight of grain. Lay out your pieces accordingly. Some pieces will be cut on the fold. This is noted on the pattern piece. Mark all notches and other design features such as pleats etc. from the pattern onto your fabric.

When sewing the garment, pay attention to notches, they must match up.

Main fabric:

1. Back – cut 1 on fold
2. Front – cut 2
3. Sleeve – cut 2
4. Pocket – cut 2
5. Belt – cut 1

INSTRUCTIONS:

1. Sew darts on front. Press bulk towards bottom.
2. Turn upper seam allowance on pocket under and topstitch. Fold inside inside side and lower seam allowances and press. Topstitch pocket according to markings onto front.
3. Pin fronts together right sides together. Sew collar seam, press seam apart. Sew and press apart shoulder seams, serge. Clip into seam allowance of shoulder seam on front and sew collar into back neckline, press seam apart.
4. Sew sleeves into armholes matching notches, press seam.
5. Sew side seams processing the sleeve seam at the same time, press seams towards back.
6. Fold belt in half lengthwise, right sides together, and sew along long side and one short side. Turn belt right side out, turn seam allowances along unsewn edge under and sew a decorative stitch at 0.7 cm from edge around the belt.

TECHNICAL DRAWING:

