

Quilted Vest - Sewing Pattern #4703

Recommendations on fabric: quilted natural/mixed fabrics suitable for raincoats.

You will also need: fusible interfacing; lining; 3 buttons.

Seam allowances: all seams 1 cm.

Note on seam allowances:

- If the pattern has double contour the seam allowances are included. They are 1 cm unless specified otherwise.
- If the pattern has single contour, the seam allowances are NOT included and need to be added when laying out the pattern.

Note on length of fabric:

Attention! The amount of fabric needed for your pattern is not included. It will depend on the selected pattern size, the width, and design of the fabric you plan to use. First, print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm). Measure how much fabric you will need. Don't forget to account for pieces that need to be cut multiple times and pieces that are cut on the fold.



CUTTING:

Note on cutting:

On the pattern pieces, "beam" means straight of grain. Lay out your pieces accordingly. Some pieces will be cut on the fold. This is noted on the pattern piece. Mark all notches and other design features such as pleats etc. from the pattern onto your fabric.

When sewing the garment, pay attention to notches, they must match up.

Main fabric:

1. Center back – cut 2
2. Side back – cut 2
3. Center front - cut 2
4. Side front – cut 2
5. Buttonstand — cut 2
6. Collar — cut 4
7. Back neck facing – cut 1

Lining:

1. Center back – cut 2
2. Side back – cut 2
3. Side front – cut 2
4. Center front – cut 2
5. Pocket bag – cut 4

Attention! Lining is cut using pattern blocks for self fabric except for the area of back neckline facing and center front facing (buttonstand).

Fusible interfacing:

1. Buttonstand — cut 2
2. Collar — cut 2
3. Back neck facing – cut 1

INSTRUCTIONS:

1. Apply fusible interfacing.
2. Sew center back seam, press seam apart. Sew side backs to center back, press seam apart.
3. Apply fusible interfacing to pocket opening. Sew pocket bags to fronts. Sew side fronts to front, sewing the pocket bag at the same time. Clip into seam allowances near pocket opening, serge seam allowances of princess seams apart, pocket press towards center.
4. Sew shoulder and side seams, press seam apart.
5. Sew center seams on collars, press seam apart. Pin collars together right sides together and sew collar fall. Clip into curves, trim away corners. Turn collar right side out, straighten, press. Baste collar to neckline of waistcoat.
6. Sew princess seams on back lining and front lining—sew center back to side backs and sew center front to side fronts, seam allowances press towards center. Sew center back seam, press towards left. Sew back neckline facing and center front facing to lining, press towards self fabric. Sew shoulder and side seams, leaving an opening in left side seam.
7. Pin garment to lining right sides together and sew along center front, neckline and hem. Clip into seam allowances on curves, trim away corners. Turn waistcoat right side out, straighten, press.
8. Sew armhole in two steps through the opening in side seam: sew back armhole from shoulder seam to side seam and sew front armhole from shoulder seam to side seam. Sew the opening closed.
9. Make buttonholes on fronts according to markings. Sew on buttons.

TECHNICAL DRAWING:

