

## Blouse With Assymmetric Yoke - Sewing Pattern #4715

Recommendations on fabric: natural/mixed knit fabric of small stretchiness.

You will also need: knit fusible interfacing; 3 buttons.

Seam allowances: seam allowance for hem of garment – 2 cm, seam allowance on lower edge of sleeve – 1.2 cm; other seams - 0.7 cm.

Attention! Pattern blocks have markings and texts from the right side. Take this into account when cutting the fabric-some of the pattern blocks need to be laid onto fabric with their wrong side on top.

### Note on seam allowances:

- If the pattern has double contour the seam allowances are included. They are 1 cm unless specified otherwise.
- If the pattern has single contour, the seam allowances are NOT included and need to be added when laying out the pattern.



### Note on length of fabric:

Attention! The amount of fabric needed for your pattern is not included. It will depend on the selected pattern size, the width, and design of the fabric you plan to use. First, print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm). Measure how much fabric you will need. Don't forget to account for pieces that need to be cut multiple times and pieces that are cut on the fold.

## CUTTING:

### Note on cutting:

On the pattern pieces, "beam" means straight of grain. Lay out your pieces accordingly. Some pieces will be cut on the fold. This is noted on the pattern piece. Mark all notches and other design features such as pleats etc. from the pattern onto your fabric.

When sewing the garment, pay attention to notches, they must match up.

Knit fabric:

1. Back – cut 2
2. Upper left front – cut 1

3. Upper right front – cut 1
4. Lower front – cut 1
5. Left collar – cut 2
6. Right collar – cut 2
7. Sleeve – cut 2

Fusible interfacing:

1. Left collar – cut 1
2. Right collar – cut 1

## INSTRUCTIONS:

1. Apply fusible interfacing to collars.
2. Sew center back seam, press towards left and serge.
3. Sew bust dart on upper left front, trim bulk with serger. Make and topstitch pleats on upper right front according to markings (fold bulk of pleats towards side seam).
4. Sew shoulder seams, press seams towards back and serge.
5. Sew collars together by two. Pin together collar right sides together and sew along collar fall. Turn collar right side out, press.
6. Pin collar to wrong side of blouse and sew the left side along neckline up to center back, serge. Fold left end onto right side and baste together with center edge on front. Insert left front between right front and collar and sew remaining part of collar seam from center back to waist. Serge.
7. Sew upper front to lower front, serge and press towards bottom.
8. Hem of sleeve serge, press onto wrong side and topstitch. Sew sleeve into open armhole, serge and press.
9. Sew sleeve seams and continue sewing side seams, press seams towards back and serge.
10. Serge lower edge of garment, press onto wrong side and topstitch.
11. Sew decorative buttons onto right upper front.

**TECHNICAL DRAWING:**

