

## Long Jacket - Sewing Pattern #4713

Recommendations on fabric: neoprene or other stable fabric.

You will also need: buckle.

Seam allowances: all seams 1 cm. Seam allowance along hem, center front and neckline – 0 cm.

Attention: pattern blocks have markings and texts from the right side. Take this into account when cutting the fabric - some of the pattern blocks need to be laid onto fabric with their wrong side on top..

### Note on seam allowances:

- If the pattern has double contour the seam allowances are included. They are 1 cm unless specified otherwise.
- If the pattern has single contour, the seam allowances are NOT included and need to be added when laying out the pattern.

### Note on length of fabric:

Attention! The amount of fabric needed for your pattern is not included. It will depend on the selected pattern size, the width, and design of the fabric you plan to use. First, print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm). Measure how much fabric you will need. Don't forget to account for pieces that need to be cut multiple times and pieces that are cut on the fold.



## CUTTING:

### Note on cutting:

On the pattern pieces, “beam” means straight of grain. Lay out your pieces accordingly. Some pieces will be cut on the fold. This is noted on the pattern piece. Mark all notches and other design features such as pleats etc. from the pattern onto your fabric.

When sewing the garment, pay attention to notches, they must match up.

Main fabric:

1. Center back – cut 1
2. Side back – cut 2

4. Center front – cut 2
5. Side front – cut 2
6. Belt – cut 2

### **INSTRUCTIONS:**

1. Sew side backs to center back. Press seam apart.
2. Sew side fronts to center front, press seam apart.
3. Thread buckle into belt, fold belt in half and sew to left side edge. Sew the other end of the belt to right center front.
4. Sew and press apart side and shoulder edges of jacket.

### **TECHNICAL DRAWING:**

