

Knit Jacket With Round Pockets - Sewing Pattern #4727

Recommendations on fabric: natural/mixed knit fabric of small stretchiness.

You will also need: rib knit fabric for pockets; knit fusible interfacing; separating zipper; 2 non separating zippers; 4 buttons.

Seam allowances: all seams 1 cm. Seam allowance of sleeve hem – 2 cm.

Note on seam allowances:

- If the pattern has double contour the seam allowances are included. They are 1 cm unless specified otherwise.
- If the pattern has single contour, the seam allowances are NOT included and need to be added when laying out the pattern.

Note on length of fabric:

Attention! The amount of fabric needed for your pattern is not included. It will depend on the selected pattern size, the width, and design of the fabric you plan to use. First, print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm). Measure how much fabric you will need. Don't forget to account for pieces that need to be cut multiple times and pieces that are cut on the fold.



CUTTING:

Note on cutting:

On the pattern pieces, "beam" means straight of grain. Lay out your pieces accordingly. Some pieces will be cut on the fold. This is noted on the pattern piece. Mark all notches and other design features such as pleats etc. from the pattern onto your fabric.

When sewing the garment, pay attention to notches, they must match up.

Main fabric:

1. Back yoke – cut 1
2. Center back – cut 2
3. Side back – cut 2
4. Lower back – cut 2
5. Lower front – cut 4

6. Side front – cut 2
7. Center front – cut 2
8. Center front – cut 2
9. Front yoke – cut 2
10. Pocket bag – cut 2
11. Placket – cut 2
12. Upper sleeve – cut 2
13. Lower sleeve – cut 2
14. Hood – cut 2
15. Center hood – cut 1
16. Buttonstand – cut 2
17. Strap – cut 2
18. Pocket placket – cut 2

Fusible interfacing:

1. Lower back – cut 1
2. Lower front – cut 2
3. Placket – cut 2
4. Buttonstand – cut 2

INSTRUCTIONS:

1. Apply fusible interfacing.
2. Sew center back seam, press towards left, serge and topstitch at 0.5 cm from seam. Sew back yoke to yoke, press towards top, serge and topstitch at 0.5 cm from seam. Sew side back to lower back, press seam apart and serge. Sew side back and lower back to back, press towards side seam and serge.
3. Cut pocket placket from rib knit fabric, press it in half lengthwise right side out. Press pocket placket easing it in according to the shape of pocket opening.
4. Pin pocket bag onto right side of middle front, insert rib knit facing between them and sew pocket opening. Fold pocket bag onto wrong side, press. Pin the piece onto middle front and baste together along edges. Sew edges of pocket bags, serge.
5. Sew front yoke to front, press towards top, serge and topstitch at 0.5 cm from seam. Sew side front to lower front, press seam apart and serge. Sew side front and lower front to front, press towards side seam and serge.
6. Sew shoulder seams, press seams towards back and serge. Sew side seams from armhole to notch, seam allowances near notch clip, press apart and serge.
7. Fold placket in half lengthwise right sides together and sew lower corner. Turn right side out placket onto right

side, straighten, press. Serge inner edges of front center facings. Pin outer side of right placket to right front right sides together and sew. Sew right center front facing to inner side of placket, inserting zipper between the pieces. Pin outer side of left placket to left front right sides together, insert zipper between the pieces and sew. Sew left center front facing to inner side of placket.

8. Sew side hoods to center hood, press seam allowances towards center part and serge. Serge inner edge of hood facing. Pin facing onto hood and sew outer edge. Clip into curves, turn facing under, press. Topstitch facing onto hood.

9. Sew hood into neckline, press seam, serge. Sew front center facings into seam of hood. Turn garment right side out, press.

10. Sew seam on upper sleeve, serge and press. Sew zipper to lower sleeve, forming a ring. Sew upper sleeve to lower sleeve, press towards top and serge.

11. Sew sleeves into armholes matching notches, serge and press.

12. Serge upper edges of inner lower back and inner lower front. Pin the pieces onto garment and sew lower edge. Clip into curves, fold inner parts onto wrong side and stitch in the ditch.

13. Serge lower edge of sleeve, press onto wrong side and topstitch.

14. Pin together strap in half lengthwise right sides together and sew around all edges, leaving an opening for turning. Trim away corners, turn right side out strap onto right side, sew the opening closed. Topstitch strap at side seam, sew on buttons.

TECHNICAL DRAWING:

