

Sweatshirt - Sewing Pattern #4751

Recommendations on fabric: natural/mixed knit fabric of small stretchiness.

You will also need: zipper.

Seam allowances: all seams 1 cm. Seam allowance on left and right front near pocket opening – 2 cm. Seam allowance along hem of back, hem of front and hem of sleeve – 2.0 cm.

Note on seam allowances:

- If the pattern has double contour the seam allowances are included. They are 1 cm unless specified otherwise.
- If the pattern has single contour, the seam allowances are NOT included and need to be added when laying out the pattern.

Note on length of fabric:

Attention! The amount of fabric needed for your pattern is not included. It will depend on the selected pattern size, the width, and design of the fabric you plan to use. First, print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm). Measure how much fabric you will need. Don't forget to account for pieces that need to be cut multiple times and pieces that are cut on the fold.

Note on working with stretchy fabric:

Knitted fabric pieces are sewn together with special elastic or narrow zig-zag stitch. Seam allowance on hems can be stitched with twin needles to save stretchiness. Pieces can also be sewn together with a serger. When serging, cut seam allowances to 0.6 – 0.8 cm.

CUTTING:

Note on cutting:

On the pattern pieces, "beam" means straight of grain. Lay out your pieces accordingly. Some pieces will be cut on the fold. This is noted on the pattern piece. Mark all notches and other design features such as pleats etc. from the pattern onto your fabric.

When sewing the garment, pay attention to notches, they must match up.

Main fabric:

1. Back – cut 1 on fold



2. Front right - cut 1
3. Front left - cut 1
4. Back sleeve - cut 2
5. Front sleeve - cut 2
6. Stand collar - cut 2
7. Pocket bag - cut 2

INSTRUCTIONS:

1. Serge side and inner edges of pocket bag. Clip into seam allowances near notches of side seam on left and right front. Press seam allowance of pocket opening two times at 1 cm and topstitch. Pin front onto pocket bag and topstitch along the marked line.
2. Serge lower edges of fronts, press onto wrong side and topstitch. Pin right side of right front to wrong side of left front and sew the neckline. Clip seam allowances, turn pieces right side out, baste together along raw edges and treat as one piece in the future.
3. Sew Back Sleeve to Back, press seams towards back and serge.
4. Sew upper edges of sleeves, press seams towards back and serge.
5. Sew outer stand collar into neckline, press seam allowances towards stand collar.
6. Sew right front sleeve to front, press towards front and serge. Sew left front sleeve to front from notch to side seam, clip into seam allowance near the notch, press apart and serge. Sew in zipper.
7. Sew side seams, sewing the sleeve edges at the same time, press seams towards back and serge.
8. Serge lower edge of inner stand collar. Pin inner collar stand to outer collar stand right sides together and sew side edges and upper edge. Trim away corners, turn stand collar right side out, press. Stitch-in-the-ditch the inner stand collar into the seam between outer stand collar and self garment.
9. Serge hem of sleeve, press onto wrong side and topstitch. Serge lower edge of sleeve, press onto wrong side and topstitch.

TECHNICAL DRAWING:

