

Sewing Pattern — Coat 4071

Recommendations on fabric: whipcord

You will also need: lining, warmer (isofort, polyester batting), separable zipper (length is shown on front pattern), elastic of 1.5 – 2 cm wide, elastic for belt of 7 cm wide, decorative clasps of 7 cm wide for belt, 5 big snaps, 2 eyelets, cord for hood, 2 caps for cord, 2 limiters for cord.

Seam allowances: on lining edges - 1 cm, hem of sleeve – 3 cm, all other seams – 1.5 cm.

Note on seam allowances:

- If the pattern has double contour the seam allowances are included. They are 1 cm unless specified otherwise.
- If the pattern has single contour, the seam allowances are NOT included and need to be added when laying out the pattern.

Note on length of fabric:

Attention! The amount of fabric needed for your pattern is not included. It will depend on the selected pattern size, the width, and design of the fabric you plan to use. First, print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm). Measure how much fabric you will need. Don't forget to account for pieces that need to be cut multiple times and pieces that are cut on the fold.

CUTTING:

Main fabric:

1. Back yoke - cut 1
2. Center back — cut 1
3. Side back – cut 2
4. Lower back – cut 1
5. Front yoke – cut 2
6. Center front — cut 2
7. Side front – cut 2
8. Lower front – cut 2
9. Sleeve – cut 2
10. Center hood – cut 2
11. Side hood – cut 4
12. Welt – cut 4
13. Belt – cut 1
14. Wind placket – cut 2
15. Back neck facing – cut 1
16. Front facing – cut 2
17. Inner placket – cut 2
18. Belt loop – cut 1



Lining:

1. Center front – cut 2
2. Side front – cut 2
3. Front yoke – cut 2
4. Center back – cut 1
5. Side back – cut 2
6. Back yoke – cut 1
7. Sleeve – cut 2
8. Sacking – cut 4

Warmer:

1. Back yoke - cut 1
2. Center back — cut 1
3. Side back – cut 2
4. Lower back – cut 1
5. Front yoke – cut 2
6. Center front — cut 2
7. Side front – cut 2
8. Lower front – cut 2
9. Sleeve – cut 2
10. Center hood – cut 1
11. Side hood – cut 2
12. Welt – cut 2
13. Wind placket – cut 1
14. Inner placket – cut 1

Note:

1. Cut lining hood from main fabric.
2. Sleeve warmer comes to hem turnout line.
3. Lining and warmer pieces for yoke are cut using main fabric pattern pieces.
4. Before sewing please check fabric care to heat and wet treatment.

INSTRUCTIONS:

1. Topstitch yokes, center and side backs and fronts as well as hood and sleeve details onto corresponding warmer details. Topstitch placket and welt details onto warmer. Stitch on long and one short sides of wind and inner plackets. Turn details out, press and stitch at 0.7 cm from the seam.
2. Sew together warmer details of lower back and front with whip stitch. Sew together main details of back and front. Press seam toward back. Make gathering stitch along upper and lower edges of lower front and gather ruffle so the edge is equal to warmer edge. Topstitch upper edge of lower part onto warmer, turn warmer round and topstitch ruffle onto upper edge from wrong side.
3. Topstitch elastic, slightly stretching it, onto center and side fronts from the wrong side, at pocket opening level. (Elastic length is shown on pattern pieces).
4. Sew welt with sacking to center front. Sew sacking to side front. Sew center and side fronts, sewing sacking at the same time. Press seam toward center and stitch at 0.7 cm from the seam. Make gathering stitch on upper edge of front and make ruffle. Sew yoke to front. Press seam upwards.
5. Sew side backs to center back. Press seam toward back center and stitch at 0.7 cm from the seam. Make gathering stitch on upper edge of back and make ruffle. Sew yoke to back. Press seam upwards.

6. Topstitch elastic, slightly stretching it, on back, front and sleeve details from the wrong side. (Elastic length is shown on pattern pieces).
7. Sew shoulder and side edges. Press seams apart.
8. Sew hood details. Press seam toward center part and stitch at 0.7 cm. Set eyelets according to marks. Sew hood details into neck. Press seam.
9. Topstitch left half of zipper onto inner placket, matching tape edge and open edge of placket. Sew placket with zipper to left front band. Sew right half of zipper to right front.
10. Sew sleeve edge. Sew sleeve on curve, matching notches.
11. **Lining:** Sew separately back details, front details and hood details. On back neck facing and front facings – press outer edge inside and topstitch facing and front facing onto back and front correspondingly. Sew shoulder edges. Sew sleeve into open armhole. Sew side seam, continuing as sleeve seam and leaving an opening in left sleeve. Sew hood into neckline.
12. Fold belt loop detail in half lengthwise, right side together and stitch on long edge. Turn out, press and cut into two pieces. Sew belt loops near side seams at waist line.
13. Make gathering stitch along lower edge of main detail and make ruffle so the length is equal to lower part length. Sew lower back and front to lower edge of coat.
14. Close front band edge with lining, closing hood at the same time. Fasten together allowances of hood connecting seam on main and lining details. Make decorative stitch along front band at 0.7 cm from the edge. Make decorative stitch along hood edge at 3 cm. Sew lining to ruffle connecting seam. Sew lining to hem of sleeve. Sew the opening in sleeve closed.
15. Punch snaps on wind placket. Topstitch wind placket onto right front according to marks. Punch snaps on left front.
16. Fold belt detail in half lengthwise right side together and stitch on long side. Turn out. Set elastic in, fasten it at side edges and make fastening stitch along center of belt. Set ends of belt into clasp and regulate length. Turn ends inside and topstitch. Set belt through the loops.
17. Set cord into hood, set limiters and put caps on.

TECHNICAL DRAWING:

