

Sewing Pattern — Skirt 4069

Recommended fabric: light-weight suiting fabric.

If the pattern has a double line around it, the seam allowances are included.

Seam allowance: 1 cm on all edges, hem – 3 cm, central back seam – 1.5 cm.

Note: By default, seam allowances are NOT included (single line) and will need to be added when laying out and cutting details.

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to take into account pieces to be duplicated or cut on a fold.

When sewing the garment, pay attention to notches, they must coincide.



CUTTING:

(On the pattern pieces, “beam” means straight of grain. Lay out your pieces accordingly. Some pieces will be cut on the fold. This is noted on the pattern piece (*bending). Mark all notches and other design features such as darts, pleats etc. from the pattern onto your fabric.)

Darts: The fold of the dart is always pressed toward the center of your garment, or down toward the hem.

Main fabric:

1. Back – cut 2
2. Upper front – cut 1
3. Lower front – cut 1
4. Back facing – cut 2
5. Front facing – cut 1
6. Flounce_1 – cut 2
7. Flounce_2 – cut 2
8. Flounce_3 – cut 2
9. Flounce_4 – cut 2

Fusible interfacing:

1. Back facing – cut 2
2. Front facing – cut 1

INSTRUCTIONS:

1. Apply fusible interfacing to facings.
2. Sew darts on back, press towards center.
3. Serge center back edges separately. Sew together from zipper marker to slit marker. Press the seam apart including the opening for the zipper. Sew in zipper.
4. Place Flounce_4, right sides together, and sew lower edge from sharp corner to marker “o”. Trim seam allowances near marker. Turn the flounce right side out, adjust and press. Fold the flounce along marked line, pin along the upper edge.
5. Place Flounce_3, right sides together, and sew lower edge, sandwiching inside Flounce_4. Turn the flounce right side out, adjust and press. Fold the flounce along marked line, pin along the upper edge.
6. Place Flounce_2, right sides together and sew lower edge, sandwiching inside Flounce_3. Turn the flounce right side out, adjust and press. Fold the flounce along marked line, pin along the upper edge.
7. Place Flounce_1, right sides together, and sew lower edge, sandwiching inside Flounce_2. Turn the flounce right side out, adjust and press. Fold the flounce along marked line, pin along the upper edge.
8. Sew together upper and lower front parts, sandwiching inside Flounce_1. Serge and press the seam upwards.
9. Topstitch the the flounces from right side seams into the lower front to the first marker.
10. Sew side seams, serge and press onto back piece.
11. Sew side seams of facings. Serge lower edge. Put together facing with skirt, right sides together, and sew seam. Understitch seam allowances onto facing 0.2 cm off the seam. Fold facings to wrong side, press. Fold inside back edges of facings and handstitch to zipper.
12. Serge bottom edge together with edge of lower front, press under and hem.

TECHNICAL DRAWING:

