

## Sewing Pattern — Dress 4068

Recommendations on fabric: thin fabric suitable for costumes.

You will also need: fusing, invisible zipper.

If the pattern has double contour, seam allowances are included.

Seam allowances are NOT included by default and need to be added when laying out and cutting details if your pattern has single contour.

Seam allowance 1 cm on all edges. Hem 3 cm. Inner edge of slit – 0 cm.

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.

### **CUTTING:**

Fabric:

1. Back part – 2 details.
2. Front part – 1 detail.
3. Front fly piece – 1 detail.
4. Back facing – 2 details.
5. Front facing – 1 detail.
6. Left part of fly piece – 1 detail.
7. Bow – 2 details.
8. Interjoining – 1 detail.
9. Slit facing – 2 details.

Fusing:

1. Back facing – 2 details.
2. Front facing – 1 detail.
3. Slit facing – 2 details.



---

## **INSTRUCTIONS:**

1. Apply fusing to facings.
2. Sew darts on back part, press depths to center.
3. Serge central edges of back part. Sew central seam from zipper marker to slit marker. Press apart seam allowances and slit. Sew in zipper.
4. Serge outer edges of slit facings. Overstitch slit with facings from marker to hem. Overstitch lower corner of slit exactly along the marked line of the hem's fold. Slash seam allowances. Turn facing to the wrong side.
5. Serge upper, diagonal and lower edges on fly piece. Overstitch lower corner, turn to the right side. Press serged edges to the wrong side and topstitch: upper and diagonal edges by 0.2 cm, lower 0.3 cm off the edge. Make plaits on middle edge to achieve required length, fasten and serge. Put fly piece onto front back and fasten along side seam (pay attention to the fact that side edge of fly piece is shorter by 1 cm on the top and by 0.3 cm on the bottom).
6. Serge left part of fly piece along upper and lower edges. Press upper and lower edges onto wrong side and topstitch 0.2 cm off the edge. Put left fly piece onto front part between markers on side seam, make plaits to achieve the required length, fasten, tack and sew to the right fly piece. Press apart seam allowances.
7. Sew side seams, serge and press onto back part.
8. Sew side seams of facings. Serge lower edge of facing. Put facing onto skirt right sides together and overstitch upper edge. Topstitch seam allowances onto facing 0.2 cm off the seam. Turn facing to the wrong side and press. Fold central edges of facing and sew to zipper band.
9. Serge hem, press onto wrong side and topstitch 3 cm off the edge according to the technical drawing, fixing the facing in place.
10. Put together details of bow right sides together and overstitch along perimeter, leaving a slit for turning out in the middle of upper or lower edge (so that it won't be visible under interjoining). Slash seam allowances in corners, turn bow the right side out, press and stitch the slit.
11. Sew longer sides of interjoining, press apart seam allowances, placing seam on the center of the detail. Serge short edges. Fold the interjoining around the seam connecting fly pieces and sew interjoining into a ring. Thread in bow and fasten. Fasten the interjoining to front part according to notches.

**TECHNICAL DRAWING:**

