

## Sewing Pattern — Blouse 4062

Recommended fabric: silk fabric of natural or mixed fibers.

You will also need: bias tape; narrow elastic for gathering the center upper front.

If the pattern has a double line around it, the seam allowances are included.

Seam allowance: on hem - 1.5 cm; on hem of sleeve - 3 cm; other seams - 1 cm.

**Note:** By default, seam allowances are NOT included (single line) and will need to be added when laying out and cutting details.

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to take into account pieces to be duplicated or cut on a fold.

When sewing the garment, pay attention to notches, they must coincide.



### **CUTTING:**

(On the pattern pieces, “beam” means straight of grain. Lay out your pieces accordingly. Some pieces will be cut on the fold. This is noted on the pattern piece (\*bending). Mark all notches and other design features such as darts, pleats etc. from the pattern onto your fabric.)

### **Main fabric:**

1. Upper front – cut 1
2. Back – cut 2
3. Lower front – cut 1

### **INSTRUCTIONS:**

1. Sew center back seam. Serge and press toward left.
2. Along center of upper front, sew elastic, stretching it to create gather.
3. On top edge of lower front, sew a gathering stitch between markings, and gather. Sew lower front to upper front. Serge and press.
4. Sew side/underarm seam. Serge and press towards back.
5. Sew shoulder seams. Serge and press toward back.
6. Cut bias tape of length equal to neckline length + 2 cm. Fold the bias tape in half lengthwise and press. Apply bias tape, right sides together, along neck edge. Turn the bias tape to wrong side, pin and topstitch.

7. Turn hem of sleeve twice inside to 1.5 cm, and topstitch.
8. Serge hem of garment. Turn under, press and topstitch.

**TECHNICAL DRAWING:**

