

## Sewing Pattern — Blouse 4056

Recommendations on fabric: fabric suitable for blouse, a little stretchy.

You will also need: fusing, 6 buttons.

Seam allowances are NOT included and need to be added when laying out and cutting details.

Seam allowance 1 cm on all edges, on hem – 1.5 cm, on necklines and long edges of ruche – 0.7 cm.

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



### **CUTTING:**

Fabric:

1. Front part – 2 details
2. Back part – 2 details
3. Sleeve – 2 details
4. Ruche – 1 folded detail
5. Sleeve facing – 2 details

Fusing:

1. Wholecut front facing/buttonstands

### **INSTRUCTIONS:**

1. Apply fusing to wholecut front facings/buttonstands and the place for buttonhole near the edge of neckline.
2. Sew darts on back and front details. Press depths towards center.
3. Sew middle back seam. Serge and press to the left.
4. Sew side and shoulder seams. Serge and press towards back part.
5. Cut bias tape 3 cm wide and of the length equal to the length of neckline.
6. Fold ruche in half lengthwise right sides together and sew the short edges. Turn the right side out and press. Stitch loosely along the outer edge of ruche and gather ruffles. Make two buttonholes into front part (for threading in cord). Put bias tape onto neckline and stitch, putting ruche between them (short edge of ruche reaches edge of buttonstand). Fold inside lower edge of bias tape and press.
7. Serge hem.

8. Press buttonstand inside first by 1 cm and then by width of buttonstand. Fold buttonstand onto right part and overstretch upper and lower edges.
9. Fold buttonstand to the wrong side and topstitch. Stitch along the lower edge of bias tape, forming a half-belt. Begin stitching at the topstitch of the buttonstand.
10. Fold sleeve facing in half lengthwise wrong sides together and press. Stitch loosely along the seam allowance of the facing. Gather ruffles. Stitch facing to the sleeve. Serge the seam and press upwards. Sew sleeves into armholes. Serge armhole. Fold seam allowances of the lower part of armhole inside and topstitch.
11. Cut a cord 2-2.5 cm wide. Fold in half lengthwise wrong sides together and press. Fold apart, press side edges towards center and fold in half. Stitch 0.1 cm off the edge.
12. Fold hem to the wrong side and topstitch. Press the seam.
13. Make buttonholes into right front part. Sew on buttons onto left front part. Thread cord into half-belt.

**TECHNICAL DRAWING:**

