

Sewing Pattern — Blouse 4052

Recommendations on fabric: natural / mixed blouse fabrics.

You will also need: elastic yarn.

If the pattern has double contour the seam allowances are included.

Seam allowances are NOT included by default and need to be added when laying out and cutting details if your pattern has single contour.

Seam allowance: along the edge of the garment 2 cm; on top edge of back part, of front part and of sleeve – 3 cm; along the edge of sleeve — 4 cm, all other seams - 1 cm

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



CUTTING:

Main fabric:

1. Sleeve - 2 details
2. Back – front part – 2 details

INSTRUCTIONS:

1. Stitch sleeve along armhole to back -front part. Serge the seam and press to sleeve.
2. Sew side seams of the blouse, stitching edges of sleeves at the same time. Serge seams and press towards back part.
3. Serge lower edge of the blouse, turn inside and topstitch.
4. Serge lower edge of sleeve and upper edge of the blouse, turn inside onto wrong side. Put stitches with elastic yarn.

TECHNICAL DRAWING:

