Pants With Fall-Over - Sewing Pattern #4050

Recommendations on fabric: thin well draping natural/mixed fabric suitable for dresses.



You will also need: fusible interfacing; elastic tape; 1 zipper.

Seam allowances: all seams 1 cm, seam allowance along the hem 2 cm.

Note on seam allowances:
- If the pattern has double contour the seam allowances are included. They are 1 cm unless specified otherwise.
- If the pattern has single contour, the seam allowances are NOT included and need to be added when laying out the pattern.

Note on length of fabric:
Attention! The amount of fabric needed for your pattern is not included. It will depend on the selected pattern size, the width, and design of the fabric you plan to use. First, print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm). Measure how much fabric you will need. Don't forget to account for pieces that need to be cut multiple times and pieces that are cut on the fold.

CUTTING:

Note on cutting:
On the pattern pieces, “beam” means straight of grain. Lay out your pieces accordingly. Some pieces will be cut on the fold. This is noted on the pattern piece. Mark all notches and other design features such as pleats etc. from the pattern onto your fabric.
When sewing the garment, pay attention to notches, they must match up.

Main fabric:
1. Back half – cut 2
2. Front half – cut 2
3. Back facing – cut 1
4. Front facing right – cut 1
5. Front facing left – cut 1
6. Button catch (zipper facing) – cut 1
7. Side – cut 2
8. Pocket bag – cut 2

Fusible interfacing: front facing left and right, back facing, button catch (zipper facing).

INSTRUCTIONS:

1. Apply fusible interfacing to the back facing, right and left front facings, and fly shield.

2. Stitch the side seams of the front and back facings. Press Apart side seams of facings. Serge lower edge.

3. Mark and sew the darts on the back half of the pants. Press darts towards center. Sew center seam on back halves, press towards left and serge.

4. Form and secure the pleats on the front piece according to the markings. Pin pocket bag onto front half and sew pocket opening. Clip into curves, fold pocket bag onto wrong side, topstitch seam allowances onto pocket bag at 0.1 cm and press.

5. Pin front half onto side according to markings. Sew pocket bag to side, serge. Secure the pocket bag to the front piece along the upper and side edges.

6. Trim off the cut-on facing from the left front piece, leaving a 1.5 cm seam allowance. Serge the center edges of the front pieces together with the cut-on facings. Stitch the center front seam from the lower edge to the beginning of the fly opening, then press the seam allowances towards the right side seam.

7. Press the cut-on zipper facings to the wrong side: on the right, along the center front line; on the left, 5 mm before the center front line. Stitch the zipper under the edge of the left closure allowance, close to the edge, positioning the zipper teeth directly against the fold. Serge the long edges and lower edge of the fly shield. Place the unfolded fly shield underneath the left closure allowance and topstitch close to the zipper attachment seam. Spread out the front pieces and straighten the closure edge. Match the center front lines and secure them together. Stitch the free zipper tape to the cut-on facing of the right front piece without catching the main fabric.

8. Sew side seams, seam allowances press towards back and serge. Sew the inside leg edges, seam allowances press towards back and serge.

9. Stitch the facing to the cut-on facing of the right front piece and to the fly shield on the left. Place the facing and trousers right sides together and stitch along the upper edge. Trim the seam allowances at the corners and turn the facing to the wrong side. Understitch the seam allowances onto the facing, 0.1 cm from the seam.

10. Topstitch the right front piece along the zipper according to the markings, stopping 3 cm before the lower end of the zipper. Close the zipper and continue the topstitching, curving around the lower end of the closure and catching the fly shield.

11. Serge the trouser hem allowance, press it to the wrong side and topstitch, leaving openings for the elastic.

Insert the elastic.

TECHNICAL DRAWING:

