

Sewing Pattern — Blouse 4042

Recommended fabric: natural / mixed knit fabrics of medium to high stretchiness.

If the pattern has a double line around it, the seam allowances are included.

Seam allowance: on hem of sleeve – 1.5 cm, all other seams 0.8 cm.

Note: By default, seam allowances are NOT included (single line) and will need to be added when laying out and cutting details.

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to take into account pieces to be duplicated or cut on a fold.

When sewing the garment, pay attention to notches, they must coincide.



CUTTING:

(On the pattern pieces, “beam” means straight of grain. Lay out your pieces accordingly. Some pieces will be cut on the fold. This is noted on the pattern piece (*bending). Mark all notches and other design features such as darts, pleats etc. from the pattern onto your fabric.)

Advice: Knit fabric pieces are sewn together with special elastic or narrow zig-zag stitch. Seam allowance on hem is stitched with twin needles to save stretchiness. Pieces can also be sewn together with 3 or 4 – thread serger. When serging, cut seam allowances to 0.6 – 0.8 cm.

Main fabric:

1. Back– cut 1 on fold
2. Front – cut 2
3. Sleeve – cut 2
4. Front yoke – cut 2

INSTRUCTIONS:

1. Sew center front seam up to the mark for collar. Serge and press toward left.
2. Sew yoke to front. Serge the seam and press downwards.
3. Sew shoulder seams, serge and press towards back.

4. Cross collar over as shown in picture and sew center front seam. Press the seam open. Fold collar in half lengthwise and sew into the neckline. Serge and press the seam. (Do not sew the section between two closest markers. This part is required to cross the collar over.)
5. Sew sleeve into armhole. Serge and press the seam. Sew side seam and sleeve seam as one. Serge and press the seam toward back.
6. Serge hem of garment and lower edge of sleeve. Turn under, press and topstitch.

TECHNICAL DRAWING:

