

## Jacket - Sewing Pattern #2049

Recommendations on fabric: natural/mixed suiting fabrics.

You will also need: fusible interfacing; lining; thin shoulder pads; 3 buttons; 1 inner button.

Seam allowances: all seams 1 cm. Seam allowance on lower edge of sleeve 3 cm.

### Note on seam allowances:

- If the pattern has double contour the seam allowances are included. They are 1 cm unless specified otherwise.
- If the pattern has single contour, the seam allowances are NOT included and need to be added when laying out the pattern.

### Note on length of fabric:

*Attention! The amount of fabric needed for your pattern is not included. It will depend on the selected pattern size, the width, and design of the fabric you plan to use. First, print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm). Measure how much fabric you will need. Don't forget to account for pieces that need to be cut multiple times and pieces that are cut on the fold.*



## CUTTING:

### Note on cutting:

*On the pattern pieces, "beam" means straight of grain. Lay out your pieces accordingly. Some pieces will be cut on the fold. This is noted on the pattern piece. Mark all notches and other design features such as pleats etc. from the pattern onto your fabric.*

*When sewing the garment, pay attention to notches, they must match up.*

Main fabric:

1. Back - cut 2
2. Front - cut 2
3. Belt - cut 2 on fold
4. Center front facing — cut 2
5. Back neck facing - cut 1
6. Upper sleeve - cut 2
7. Lower sleeve - cut 2

Lining is cut using pattern blocks for main fabric, except for the width of back neckline facing and buttonstands.

Lining:

1. Back - cut 2
2. Front - cut 2
4. Upper sleeve - cut 2
5. Lower sleeve - cut 2

Fusible interfacing: front, center front facing, back neck facing, belt.

## INSTRUCTIONS:

1. Apply fusible interfacing. Apply an additional stripe of fusible interfacing along back neckline and hem of sleeve.
2. Sew a gathering stitch along lower edge of front between the markings and gather fullness.
3. Sew darts on back, press bulk towards center. Sew center back seam. Press seam apart.
4. Sew shoulder and side seams of jacket. Press seam apart.
5. Sew elbow seam on sleeve. Press elbow seam apart, Press hem of sleeve. Sew and press apart front sleeve seam.
6. Sew sleeves into armholes matching notches, adjusting ease along upper side of sleeve cap. Sew shoulder pads.
7. Sew and press apart shoulder seams of back neckline facing and buttonstand. Sew together pieces of lining in the same way as you have sewn pieces from main fabric. Sew lining to facing and buttonstands.
8. Sew lining to hem of sleeve. Pin together jacket and lining right sides together, pin together, matching outer edges. Sew lining to center front facing and neckline. Turn jacket right side out.
9. Pin belts together, right sides together, and sew along lower edge and center front edge. Trim away corners and turn right side out. Sew outer belt to lower edge of jacket, fold seam allowance towards bottom. Turn under the seam allowance of inner waistband and stitch-in-the-ditch.
10. Make buttonholes and sew on buttons.

**TECHNICAL DRAWING:**

