

Sewing Pattern — Dress 4028

Recommendations on fabric: fabric suitable for dress in two contrast colors.

You will also need: fusing, 1 invisible zipper, bias tape 4 cm wide, buckle 5 cm wide.

Seam allowances are NOT included and need to be added when laying out and cutting details.

Seam allowance 1 cm on all edges. Hem – 2 cm.

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.

CUTTING:

Dark fabric:

1. Upper left back part – 1 detail
2. Lower right back part – 1 detail
3. Central front part – 1 detail
4. Belt – 1 detail

Light fabric:

1. Upper right back part – 1 detail
2. Lower left back part – 1 detail
3. Side left front part – 1 detail
4. Upper right front part – 1 detail
5. Front facing – 1 detail
6. Back facing – 2 details

Fusing: back and front facings.



INSTRUCTIONS:

1. Apply fusing to facings.
2. Sew darts on back and front parts. Press bust darts upwards, press waist darts towards center.
3. Sew together lower and upper details of back part. Serge and press upwards. Serge central seam on back part. Sew from zipper notch to bottom. Press apart, pressing the zipper slit. Sew in zipper from top edge to notch.
4. Sew upper right front part to central front part. Serge and press to central part. Sew vertical edge of plait. Serge and press apart. Sew relieve seam on front part from armhole to plait. Slash in plait corner. Serge and press towards central part. Make plait according to markers. On right side of front part stitch along the upper edge of plait, fixing it.
5. Sew shoulder seam. Serge and press towards back part.
6. Sew shoulder seams on facings. Serge and press towards front part. Serge outer edge of facings. Put together dress and facing right sides together, adjusting necklines. Step aside 0.5 cm off the invisible zipper edges, fold facing and pin to upper edge. Fold seam allowances near invisible zipper and pin to neckline on top of facing. Overstitch neckline. Slash seam allowances on rounded areas, turn inside out and press. Topstitch seam allowances onto facing. Handstitch facing to invisible zipper.
7. Cut or take bias tape 4 cm wide and of the length equal to the length of armhole + 5 cm. Fold bias tape in half lengthwise wrong sides together and press. Put bias tape to armhole from the right side and overstitch, fold bias tape to the wrong side and topstitch onto main detail along the fold. Press the seam.
8. Sew side seams of back and front parts. Serge and press onto back part. Make a fixing on side seam near armhole.
9. Serge hem and press inside. Topstitch hem.
10. Fold belt in half lengthwise right sides together and overstitch along long and short edges. Turn to the right side, fold seam allowances of the unstitched part inside and make decorative stitch 0.5 cm off the edge around the belt. Thread in and sew buckle.

TECHNICAL DRAWING:

