

Dress With Contrasting Trimming - Sewing Pattern #2133

Recommendations on fabric: well draping natural/mixed fabric suitable for dresses in contrasting colors.

You will also need: dress zipper, fusible interfacing.

Seam allowances: All seams - 1.0 cm.

Note on seam allowances:

- If the pattern has double contour the seam allowances are included. They are 1 cm unless specified otherwise.
- If the pattern has single contour, the seam allowances are NOT included and need to be added when laying out the pattern.

Note on length of fabric:

Attention! The amount of fabric needed for your pattern is not included. It will depend on the selected pattern size, the width, and design of the fabric you plan to use. First, print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm). Measure how much fabric you will need. Don't forget to account for pieces that need to be cut multiple times and pieces that are cut on the fold.



CUTTING:

Note on cutting:

On the pattern pieces, "beam" means straight of grain. Lay out your pieces accordingly. Some pieces will be cut on the fold. This is noted on the pattern piece. Mark all notches and other design features such as pleats etc. from the pattern onto your fabric.

When sewing the garment, pay attention to notches, they must match up.

Main fabric:

1. Back - cut 2
2. Front - cut 2
3. Large pocket bag - cut 2
4. Small pocket bag - cut 2

Main fabric 1:

1. Center placket - cut 4

2. Armhole facing - cut 4
3. Belt - cut 1
4. Hem trimming - cut 1 on fold
5. Off-set welt - cut 2

Fusible interfacing:

1. Center placket - cut 2
2. Armhole facing - cut 2

INSTRUCTIONS:

1. Apply fusible interfacing.
2. Sew darts on front and on back. Press bulk of waist darts towards center, press bulk of bust darts towards top.
3. Mark the position of pocket. Press welt in half lengthwise wrong sides together. Topstitch small pocket bag onto inner side of welt. Sew welt to front along lower marked line of pocket. Sew large pocket bag to front along upper marked line of pocket. Stop stitching near short marking lines of the pocket. Slash through pocket opening. Snip diagonally toward end of stitching at 1-1.5 cm from end of pocket opening. Turn welt and large pocket bag onto wrong side through the resulting opening. Sew a double back stitch lines near corners to fix ends of pockets. Sew together edges of pocket bags, serge.
4. Sew shoulder and side seams. Serge seams and press towards back.
5. Pin center plackets together, right sides together and sew outer edge. Clip into curves, turn the piece right side out, press. Sew plackets together from notch to bottom. Sew placket to center front edge and to neckline, press towards self garment and serge.
6. Sew side seam of armhole facings, press seam apart. Pin armhole facings together, right sides together and sew outer edge. Clip into curves, turn the piece right side out, press. Sew facing to armhole, press towards self garment and serge.
7. Serge center back edges separately. Sew center back seam from notch for zipper to bottom. Sew in zipper.
8. Sew lower facing into a ring. Press seam apart. Fold facing in half lengthwise, wrong sides together and press. Sew facing to hem of dress. Serge and press towards top.
9. Fold belt in half lengthwise **посередине** and sew around all edges, leaving an opening for turning. Trim away corners, turn right side out and press. Sew the opening closed.

TECHNICAL DRAWING:

