

## Knit Jumper Without Front Dart (No Big Sizes) - Sewing Pattern #2180

Recommendations on fabric: natural/mixed knit fabric of small stretchiness.

You will also need: rib knit fabric or knit fabric of high stretchiness.

Seam allowances: all seams 1 cm.

### Note on seam allowances:

- If the pattern has double contour the seam allowances are included. They are 1 cm unless specified otherwise.
- If the pattern has single contour, the seam allowances are NOT included and need to be added when laying out the pattern.

### Note on length of fabric:

Attention! The amount of fabric needed for your pattern is not included. It will depend on the selected pattern size, the width, and design of the fabric you plan to use. First, print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm). Measure how much fabric you will need. Don't forget to account for pieces that need to be cut multiple times and pieces that are cut on the fold.

### Note on working with stretchy fabric:

Knitted fabric pieces are sewn together with special elastic or narrow zig-zag stitch. Seam allowance on hems can be stitched with twin needles to save stretchiness. Pieces can also be sewn together with a serger. When serging, cut seam allowances to 0.6 - 0.8 cm.

## CUTTING:

### Note on cutting:

On the pattern pieces, "beam" means straight of grain. Lay out your pieces accordingly. Some pieces will be cut on the fold. This is noted on the pattern piece. Mark all notches and other design features such as pleats etc. from the pattern onto your fabric.

When sewing the garment, pay attention to notches, they must match up.

Main fabric:

1. Back - cut 1 on fold
2. Front - cut 1 on fold



3. Back sleeve - cut 2
4. Front sleeve - cut 2
5. Lower sleeve - cut 2

Knit fabric **резинки**:

1. Stand collar - cut 1
2. Hem facing - cut 1 on fold
3. Cuff - cut 2

## **INSTRUCTIONS:**

1. Sew Back Sleeve to Back, press seams towards back and serge.
2. Sew Front Sleeve to Front, press towards front and serge.
3. Sew upper edges of sleeves, press seams towards back and serge.
4. Sew a gathering stitch along upper edge of lower sleeve and gather fullness. Sew lower sleeve to upper sleeve, press towards top and serge.
5. Sew side seams, sewing the sleeve edges at the same time, press seams towards back and serge.
6. Sew a gathering stitch along lower edge of sleeve and gather fullness, using the control pattern block to adjust the length. Sew cuff into a ring, press seam apart. Fold cuff in half lengthwise right side out and press. Sew cuff to lower edge of sleeve, slightly stretching it. Serge and press.
7. Sew stand collar into a ring, press seam apart. Pin together stand collar in half lengthwise right side out and press. Sew the stand collar into neckline, slightly stretching it. Serge and press.
8. Sew hem facing into a ring, press seam apart. Fold facing in half lengthwise wrong sides together and press. Sew facing to hem of garment, slightly stretching it. Serge and press.

Tip: you may use ready rib knit bands to finish the neckline, the hem and the sleeves.

## **TECHNICAL DRAWING:**

