

Dress With Asymmetrical Yoke - Sewing Pattern #2184

Recommendations on fabric: thick natural/mixed knit fabric of small stretchiness in contrasting or similar color.

You will also need: grommets; decorative cord.

Seam allowances: all seams 1 cm. Seam allowance for hem of garment - 1.5 cm.

Note on seam allowances:

- If the pattern has double contour the seam allowances are included. They are 1 cm unless specified otherwise.
- If the pattern has single contour, the seam allowances are NOT included and need to be added when laying out the pattern.

Note on length of fabric:

Attention! The amount of fabric needed for your pattern is not included. It will depend on the selected pattern size, the width, and design of the fabric you plan to use. First, print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm). Measure how much fabric you will need. Don't forget to account for pieces that need to be cut multiple times and pieces that are cut on the fold.

Note on working with stretchy fabric:

Knitted fabric pieces are sewn together with special elastic or narrow zig-zag stitch. Seam allowance on hems can be stitched with twin needles to save stretchiness. Pieces can also be sewn together with a serger. When serging, cut seam allowances to 0.6 - 0.8 cm.

CUTTING:

Note on cutting:

On the pattern pieces, "beam" means straight of grain. Lay out your pieces accordingly. Some pieces will be cut on the fold. This is noted on the pattern piece. Mark all notches and other design features such as pleats etc. from the pattern onto your fabric.

When sewing the garment, pay attention to notches, they must match up.

Main fabric:

1. Back yoke - cut 1
2. Front yoke - cut 1



3. Upper sleeve - cut 2
4. Stand collar - cut 1
5. Front inset - cut 1

Main fabric 1:

1. Back - cut 1
2. Left front - cut 1
3. Right front - cut 1
4. Lower sleeve - cut 2
5. Cuff - cut 2

INSTRUCTIONS:

1. Sew back yoke to yoke, press towards top and serge.
2. Sew front inset to left front and to right front, press seam allowances towards inset and serge. Sew front yoke to front, press towards top and serge.
3. Sew shoulder seams, press seams towards back, serge.
4. Sew upper sleeve to lower sleeve, press towards top and serge. Sew sleeves into armholes, press seam allowances towards sleeve and serge.
5. Sew side seams processing the sleeve seam at the same time, serge and press.
6. Sew cuff into a ring, press seam apart. Fold cuff in half lengthwise right side out and press. Sew cuff to lower edge of sleeve, slightly stretching it. Serge and press.
7. Sew stand collar into a ring, press seam apart. Pin together stand collar in half lengthwise right side out and press. Sew the stand collar into neckline, slightly stretching it. Serge and press.
8. Seam allowance along hem of garment serge, press onto wrong side and topstitch.
9. Install grommets according to markings. Thread in decorative cord.

Tip: you may use ready rib knit bands for finishing the neckline and lower edge of sleeves.

TECHNICAL DRAWING:

