

Bomber Jacket - Sewing Pattern #2156

Recommendations on fabric: thick natural/mixed fabrics suitable for outdoor jackets; knit fabric of high or medium stretchiness.

You will also need: fusible interfacing; lining; separating zipper.

Seam allowances: all seams 1 cm.

Note on seam allowances:

- If the pattern has double contour the seam allowances are included. They are 1 cm unless specified otherwise.
- If the pattern has single contour, the seam allowances are NOT included and need to be added when laying out the pattern.

Note on length of fabric:

Attention! The amount of fabric needed for your pattern is not included. It will depend on the selected pattern size, the width, and design of the fabric you plan to use. First, print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm). Measure how much fabric you will need. Don't forget to account for pieces that need to be cut multiple times and pieces that are cut on the fold.



CUTTING:

Note on cutting:

On the pattern pieces, "beam" means straight of grain. Lay out your pieces accordingly. Some pieces will be cut on the fold. This is noted on the pattern piece. Mark all notches and other design features such as pleats etc. from the pattern onto your fabric.

When sewing the garment, pay attention to notches, they must match up.

Main fabric:

1. Back - cut 1 on fold
2. Front - cut 2
3. Upper sleeve - cut 2
4. Lower sleeve - cut 2
5. Back neck facing - cut 1
6. Center front facing - cut 2

Knit fabric:

1. Stand collar – cut 1
2. Belt – cut 1
3. Cuff – cut 2

Lining:

1. Back – cut 1
2. Front – cut 2
3. Upper sleeve – cut 2
4. Lower sleeve – cut 2

Fusible interfacing:

1. Center front facing – cut 2
2. Back neck facing – cut 1

Attention: Front and Back from lining are cut using the pattern blocks for the main fabric except for the width of center front facing and back neckline facing correspondingly.

INSTRUCTIONS:

1. Apply fusible interfacing.
2. Sew shoulder seams, press seam apart.
3. Press stand collar in half lengthwise right side out. Sew stand collar into the back and front necklines.
4. Pin fronts right sides together and adjust edges, measure the length of center front edges. Sew zipper to the center front edge.
5. Sew shoulder edges of center front facings and back neckline facing, press seam apart. Pin center front facing onto the right side of Front and sew along the center front edge and neckline edge. When stitching make sure to place the front piece on top. Turn center front facings right side out onto right side, straighten seams and press.
6. Sew side seams, press seam apart.
7. Fold belt in half lengthwise right side out. Unfold the belt. Sew the outer part of the belt to the lower edge.
8. Sew elbow seam on sleeve, press seam apart. Sew and press apart front sleeve seam. Sew sleeves into armholes matching notches, adjusting ease along upper side of sleeve cap.

9. Sew together pieces of lining in the same way as you have sewn pieces from main fabric, leaving an opening in the lower seam of the right sleeve. Sew lining to the inner edges of center front facings, to back neckline facing and to the inner edge of belt. Turn the garment right side out through the opening in the sleeve and sew the opening closed. Sew a fixing stitch line into the seam of the belt.

10. Sew cuff into a ring. Fold cuff in half lengthwise and press wrong sides together. Sew cuffs to the bottom edge of the sleeves and of lining, serge.

Tip: you may also see ready knit bands for stand collar, belt and cuffs. In this case, when cutting make the pieces half the width.

TECHNICAL DRAWING:

