

Sewing Pattern — Tunic 4015

Recommendations on fabric: natural or mixed thin fabric.

You will also need: fusing

If the pattern has double contour the seam allowances are included.

Seam allowances are NOT included by default and need to be added when laying out and cutting details if your pattern has single contour.

Seam allowance: hem and lower edge of sleeve – 2 cm, all other edges - 1 cm

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



CUTTING:

Main fabric:

1. Front part – 1 folded detail
2. Back part – 1 folded detail
3. Sleeve – 2 details
4. Front part placket – 2 details
5. Back part placket – 2 details

Fusing:

1. Front part placket – 1 detail
2. Back part placket – 1 detail

INSTRUCTIONS:

1. Apply fusing to upper plackets of front part and back part.
2. Sew shoulder and side edges of back part and of front part, press seam onto back part and serge.
3. Sew shoulder seams of plackets. Press apart the seam. Put plackets right sides together and overstitch along inner edge. Slash seam allowances, turn onto right side and press. Stitch placket to the tunic. Serge and press the seam.
4. Sew sleeve seam. Serge and press seam allowance onto back part of sleeve. Sew sleeve into armhole. Serge seam allowance.
5. Serge lower edge of sleeve, fold seam allowance to wrong side and topstitch.
6. Serge hem of the tunic, fold seam allowance to wrong side and topstitch.

TECHNICAL DRAWING:

