

Sewing Pattern — Dress 4277

Recommendations on fabric: natural / mixed knitted fabric of medium stretchiness.

If the pattern has double contour the seam allowances are included.

Seam allowances are NOT included by default and need to be added when laying out and cutting details if your pattern has single contour.

Seam allowance: hem, lower edge of sleeve and neckline – 1.5 cm, all other seams - 0.8 cm.

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



CUTTING:

Fabric:

1. Back part – 2 details
2. Upper front part – 1 detail
3. Lower front part – 1 detail
4. Front part inset – 1 detail

Advice:

Knitted fabric details are sewn together with special elastic or narrow zig-zag stitch. When serging cut seam allowances to 0.6 – 0.8 cm. Seam allowance on turnout is stitched with twin needles to save stretchiness. Details also can be sewn together via 3 or 4 – threaded serger.

INSTRUCTIONS:

1. Sew center edge of back part. Serge and press seam allowance onto left side.
2. Stitch front part inset to upper and lower parts of the front. Serge seam allowances and press them downwards.
3. Make pleats on front part inset according to markers. Depths of the pleats are directed downwards. Fix pleats along side edge.
4. Sew shoulder and side edges. Serge seam allowances and press them towards back part.
5. Serge neckline edge. Turn seam allowance inside and topstitch.
6. Serge hem of garment, lower edge of sleeve. Fold to wrong side, press and topstitch.

TECHNICAL DRAWING:

