

## Sport Tunic - Sewing Pattern #2258

Recommendations on fabric: natural/mixed knit fabric of small stretchiness.

You will also need: zipper; decorative cord.

Seam allowances: seam allowance for hem of garment - 3 cm, seam allowance along the hood stand and the short edge of hood facing - 0 cm; all other seams 1 cm.

### Note on seam allowances:

- If the pattern has double contour the seam allowances are included. They are 1 cm unless specified otherwise.
- If the pattern has single contour, the seam allowances are NOT included and need to be added when laying out the pattern.

### Note on length of fabric:

*Attention! The amount of fabric needed for your pattern is not included. It will depend on the selected pattern size, the width, and design of the fabric you plan to use. First, print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm). Measure how much fabric you will need. Don't forget to account for pieces that need to be cut multiple times and pieces that are cut on the fold.*

### Note on working with stretchy fabric:

*Knitted fabric pieces are sewn together with special elastic or narrow zig-zag stitch. Seam allowance on hems can be stitched with twin needles to save stretchiness. Pieces can also be sewn together with a serger. When serging, cut seam allowances to 0.6 - 0.8 cm.*



## CUTTING:

### Note on cutting:

*On the pattern pieces, "beam" means straight of grain. Lay out your pieces accordingly. Some pieces will be cut on the fold. This is noted on the pattern piece. Mark all notches and other design features such as pleats etc. from the pattern onto your fabric.*

*When sewing the garment, pay attention to notches, they must match up.*

Main fabric:

1. Back - cut 1 on fold

2. Front - cut 1 on fold
3. Sleeve — cut 2
4. Cuff — cut 2
5. Pocket - cut 1
6. Hood - cut 2
7. Center hood - cut 1
8. Hood facing - cut 1

## **INSTRUCTIONS:**

1. Serge the edge of one-piece facing of the pocket opening. Fold under the pocket facing and press and topstitch. Serge pocket edges. Fold under the side and lower edges and press. Pin pocket to front, right sides together, along the upper marking line the pocket placement (the lower edge of pocket is directed towards the neckline) and sew. Fold away pocket down. Topstitch pocket onto Front along the side and lower edges.
2. Sew sleeve to back, press seam allowances towards sleeve and serge. Sew sleeve to front, press seam allowances towards sleeve and serge.
3. Serge separately the side edges and sleeve edges. Sew sleeve seam and continue to sew side seam up to the mark for slit, press seam apart. Topstitch seam allowances onto the main piece.
4. Sew center part to hoods, press seam allowances onto central part and serge. Make button holes for cord. Sew hood into neckline, serge and press.
5. Slash front in the middle between the marked lines of zipper. Make diagonal slashes at 1-1.5 cm from the end of the marking. Turn seam allowances of slit and of hood stand onto the wrong side, straighten edges. Adjust the end of the slit from the wrong side. Place zipper under the edges of the slit so that you can see the teeth. Sew the zipper.
6. Serge inner edge of hood facing. Pin facing onto hood right sides together and sew outer edge. Clip into curves, turn facing under, press. Topstitch facing onto hood.
7. Sew cuff into a ring, press seam apart. Fold cuff in half lengthwise and press right side out. Sew cuff to lower edge of sleeve, press seam allowances towards sleeve and serge.
8. Serge lower edge of garment, press onto wrong side and topstitch.
9. Thread cord into hood.

**TECHNICAL DRAWING:**

