

## Wide Pants - Sewing Pattern #2264

Recommendations on fabric: thin natural/mixed suiting fabrics.

You will also need: fusible interfacing; 1 zipper; hook and eye; lining.

Seam allowances: all seams 1 cm. seam allowance along the hem - 2.5 cm.

### Note on seam allowances:

- If the pattern has double contour the seam allowances are included. They are 1 cm unless specified otherwise.
- If the pattern has single contour, the seam allowances are NOT included and need to be added when laying out the pattern.

### Note on length of fabric:

*Attention! The amount of fabric needed for your pattern is not included. It will depend on the selected pattern size, the width, and design of the fabric you plan to use. First, print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm). Measure how much fabric you will need. Don't forget to account for pieces that need to be cut multiple times and pieces that are cut on the fold.*



## CUTTING:

### Note on cutting:

*On the pattern pieces, "beam" means straight of grain. Lay out your pieces accordingly. Some pieces will be cut on the fold. This is noted on the pattern piece. Mark all notches and other design features such as pleats etc. from the pattern onto your fabric.*

*When sewing the garment, pay attention to notches, they must match up.*

Main fabric:

1. Back half - cut 2
2. Front half - cut 2
3. Side - cut 2
4. Button catch (zipper facing) - cut 1
5. Belt - cut 1

Lining:

1. Pocket bag – cut 2

Fusible interfacing:

1. Button catch (zipper facing) – cut 1
2. Belt – cut 1

## **INSTRUCTIONS:**

1. Apply fusible interfacing. Apply a strap of fusible interfacing to the pocket opening , its width should equal 1 cm.
2. Mark and sew the darts on the back half of the pants. Press darts towards center. Serge the back center edge. Sew the center back seam and press apart.
3. Fold the front half of the pants, wrong sides together, matching the inseam edge and the side seam edge, and press the fold.
4. Pin the pocket bag onto the front half of the pants right sides together and sew pocket opening. Fold pocket bag onto wrong side and press. Sew a decorative stitch along pocket opening at 0.1 cm and press. Pin the front half of the pants onto the side piece, matching the lines of pocket opening. Sew and serge lining of pocket. Baste the side piece to the front half of the pants along the upper and the side edges.
5. Cut away the one-piece facing from the left front half, leaving a 1 cm seam allowance along the center seam. Serge center front edge and edge of zipper facing.
6. Sew the center edge of the front halves, starting stitching at the edge of the one-piece facing. Fold the one-piece facing for zipper onto wrong side and press. Match the zipper with the center edge of the left half of the pants and sew. Sew the free zipper tape to the one-piece facing of the right half. Sew a decorative stitch along the marked line on the right half of the pants at 0.1 cm. Fold the zipper facing in half lengthwise, wrong sides together, and serge the longer edge and the shorter lower edge. Sew the zipper facing to the seam of zipper tape on the left half . Sew a fixing stitch at the end of the closure from the right side of pants. Slipstitch together the lower edges of the center front facing and the button catch from the wrong side.
7. Sew side seams, press towards the back and serge. Sew the inside leg seams, press towards the back and serge.
8. Serge the lower edge of the belt. Fold belt in half lengthwise wrong sides together and press. Sew belt to upper edge of pants, sew the corners of the belt. Trim away corners, turn belt right side out. Topstitch the serged edge in to the belt seam.
9. Seam allowance for hem serge, press onto wrong side and finish with hidden stitches.
10. Sew the hook and eye onto the belt.

11. Match the side seam and the inseam and press the fold on the back pants.

**TECHNICAL DRAWING:**

