

Sewing Pattern — Skirt 4012

Recommendations on fabric: thin costume fabric, preferably with elastic fibres.

You will also need: fusing, 1 invisible zipper.

If the pattern has double contour the seam allowances are included.

If the pattern has single contour, the seam allowances are NOT included and need to be added when laying out and cutting details.

Hem seam allowance equals width of plait + 0.5 cm, all other seams – 1 cm.

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide. Text on patterns is printed on the right side.

CUTTING:

Main fabric:

1. Back part – 2 details
2. Front part – 1 detail
3. Back yoke – 4 details

Fusing

1. Back yoke – 2 details
2. Front yoke – 1 detail

INSTRUCTIONS:

1. Apply fusing to yokes.
2. Sew darts on details of back part, press depths towards center. Stitch yokes of back part to back parts. Serge seams and press upwards. Serge separately middle edges of back halves. Sew middle edges from zipper marker to slit. Press apart. Sew in zipper, press the seam. Serge lower edge.
3. Serge hem of front half, press and topstitch.
4. Sew plaits according to markers. Press plaits downwards. Starting from second plait on top, turn depth of each plait upwards to seam. Fasten plaits exactly along the marked line. Press front part.
5. Stitch yoke of front part to front part. Serge and press upwards.
6. Put together details along side edge, leveling by upper edge. Turn hem of back part upwards, wrapping front skirt part. Sew, serge and press side edges. Turn the skirt. Topstitch hem on back part. Press slit. Stitch 0.1 cm off the edge along the slit.
7. Sew side seams of inner yokes. Serge lower edge. Put together yoke with skirt right sides together and overstitch upper edge. Topstitch seam allowance on inner yoke by 0.2 cm off the



seam. Turn facings on wrong side, press. Turn inside middle edges of inner yokes and sew to band of zipper. Topstitch inner yoke & connecting seam of outer yokes.

TECHNICAL DRAWING:

