

Sewing Pattern — Jacket 4010

Please note: the model has tight sleeves

Recommendations on fabric: natural / mixed thin costume fabrics

You will also need: fusing; lining; thin shoulder pads; 3 buttons

If the pattern has double contour the seam allowances are included.

Seam allowances are NOT included by default and need to be added when laying out and cutting details if your pattern has single contour.

Seam allowance: all seams – 1cm; on hem - 3.5 cm.

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



CUTTING:

Main fabric:

1. Central back part – 2 details
2. Side back part – 2 details
3. Side front part – 2 details
4. Central front part – 2 details
5. Buttonstand – 2 details
6. Back neckline facing – 1 detail
7. Front inset of sleeve – 2 details
8. Back part of sleeve – 2 details
9. Sleeve – 2 details
10. Bottom facing of back part — 1 detail

Lining:

1. Central back part – 2 details
2. Side back part – 2 details
3. Side front part – 2 details
4. Central front part – 2 details
5. Sleeve lining – 2 details

ATTENTION: details of back part and front part from lining are cut except for the back part neckline facings width, facings hem of back part and buttonstands correspondingly

Fusing: buttonstand, back part neckline facing, hem facing of back part, central front part, side front part

INSTRUCTIONS:

1. Apply fusing to details .
2. Sew relieve edge on front part. Press apart relieve seam on front part.
3. Sew and press apart relieves on back part. Sew and press apart middle seam of back part. Sew and press apart shoulder and side seams of the jacket.
4. Sew and press apart shoulder edges of back part and buttonstand neckline facing. Stitch back part hem facing to buttonstand. Press seams apart.
5. Stitch loosely along front edge of sleeve between markers «o» and gather ruffles. Stitch front inset of sleeve. Press seam towards front seam of sleeve.
6. Stitch back inset of sleeve. Press seam towards back inset. Sew and press apart sleeve seam.
7. Sew sleeves into armholes according to notches, gathering slightly the rounding in top part. Stitch shoulder pads.
8. Sew seams on lining details and sew in sleeves, leaving a slit for turning out in left side seam. Stitch lining to inner buttonstand edges and facings.
9. Apply additional fusing forel along neckline edge of front part. Put buttonstand with facing onto right side of front part right side downwards, pin together and overstitch buttonstand, front part neckline, back part neckline and hem of the jacket. Overstitch from front part side. Topstitch seam allowance of buttonstand onto buttonstand. Stitch by 0, 2 cm off the seam.
10. Stitch lining to hem of sleeve. Turn jacket onto right side. Sew the slit.
11. Serge buttonholes on right front part, sew buttons on left front part.

TECHNICAL DRAWING: