Coat With Shawl Collar - Sewing Pattern #4007



Recommendations on fabric: natural/mixed fabric suitable for coats.

You will also need: fusible interfacing; lining; shoulder pads; sleeve heads; 5 buttons.

Seam allowances: all seams 1 cm. Seam allowance for hem of garment and hem of sleeve 3.5 cm.

Note on seam allowances:
- If the pattern has double contour the seam allowances are included. They are 1 cm unless specified otherwise.
- If the pattern has single contour, the seam allowances are NOT included and need to be added when laying out the pattern.

Note on length of fabric:
Attention! The amount of fabric needed for your pattern is not included. It will depend on the selected pattern size, the width, and design of the fabric you plan to use. First, print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm). Measure how much fabric you will need. Don't forget to account for pieces that need to be cut multiple times and pieces that are cut on the fold.

CUTTING:

Note on cutting:
On the pattern pieces, “beam” means straight of grain. Lay out your pieces accordingly. Some pieces will be cut on the fold. This is noted on the pattern piece. Mark all notches and other design features such as pleats etc. from the pattern onto your fabric.
When sewing the garment, pay attention to notches, they must match up.

Main fabric:
1. Back – cut 1 on fold
2. Front – cut 2
3. Back neck facing – cut 1
4. Center front facing – cut 2
5. Sleeve – cut 2
6. Belt – cut 1
7. Collar – cut 2
8. Pocket welt – cut 2
9. Underlay piece – cut 2

Lining:

1. Large pocket bag – cut 2
2. Small pocket bag – cut 2

Attention: The lining pieces are cut excluding the width of the center front facing and the facing. All lining seam allowances are 1 cm.

Fusible interfacing: center front facing, back neck facing, pocket welt.

INSTRUCTIONS:

1. Apply fusible interfacing to center front facing, back neckline facing, pocket welts.

2. Fold the welt in half lengthwise, right sides together, and stitch the corners. Trim the corners, turn right side out and press. Topstitch along the welt, 0.5 cm from the edge. Reinforce the pocket area with fusible interfacing. Mark a line on the welt indicating its finished width. Topstitch the small pocket bag to the inner side of the welt. Place the welt face down on the right side of the front piece along the marked line (closer to the center).. Sew off-set welt. Sew the bigger pocket bag to the other marking line of the pocket. Slash a pocket opening between the marked lines, making slashed cuts towards the corners of the marked pocket. Turn the pocket lining to the wrong side. Straighten seam allowances and press. Sew together edges of pocket bags, fixing corners of pocket. Topstitch shorter edges of pocket at 0.5 from the edge pocket welts.

3. Sew side and shoulder seams. Press the seam apart. Sew lower collar into neckline. Clip seam allowances and press apart.

5. Sew sleeve seam, press the seam apart. Set the sleeves into the armholes, easing in the sleeve caps. Sew shoulder pads and sleeve heads to garment.

6. Sew shoulder seams of back neckline facing and central front facing, press the seam apart.

7. Stitch the lining pieces together in the same way as the outer fabric pieces, leaving an opening in the side seam for turning right side out. Sew upper collar. Clip seam allowances and press apart. Sew the lining to the front central facings and to the back facing. Press the seam allowances towards the lining.

8. Place the lining and outer fabric right sides together and stitch along the front edges and collar. Secure the seam allowances of the upper and undercollar together. Stitch the lower edges of the center front facings diagonally to the front pieces towards the marked hem fold line. Trim the seam allowances at the lower front corners. Stitch along the lower edge of the coat. Turn the coat right side out. Sew a decorative stitch at 0.7 cm from the edge center front facings and of collar.

9. Sew lining to hem of sleeve. Turn coat right side out onto right side. Sew the opening closed.

10. Work 2 buttonholes on the right front piece, sew on 4 buttons and sew on the inner button.

11. Fold belt in half lengthwise, right sides together, and sew along long side and one short side. Turn belt right side out, turn under the seam allowances of the area that has not been stitched and sew a decorative stitch at 0.7 cm from the edge around the belt.

TECHNICAL DRAWING:

