

## Sewing Pattern — Coat 4007

Recommendations on fabric: natural / mixed thin coat fabrics

You will also need: fusing; lining; shoulder pads; sleeve heads; 5 buttons

If the pattern has double contour the seam allowances are included.

Seam allowances are NOT included by default and need to be added when laying out and cutting details if your pattern has single contour.

Seam allowance: all seams – 1cm; on hem of the garment and of sleeve - 3.5 cm.

**Attention!** First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



### **CUTTING:**

#### Main fabric:

1. Back part – 1 folded detail
2. Front part – 2 details
3. Back neckline facing – 1 detail
4. Buttonstand – 2 details
5. Sleeve – 2 details
6. Belt – 1 detail
7. Collar – 2 details
8. Off-set welt – 2 details
9. Underlay – 2 details

#### Lining:

1. Big pocket bag – 2 details
2. Small pocket bag – 2 details

ATTENTION: Lining details are cut excluding buttonstands and facings. All seam allowances on lining - 1 cm

Fusing: buttonstand, back part neckline facing, off-set welt

### **INSTRUCTIONS:**

1. Apply fusing to buttonstand, back neckline facing, off-set welts.
2. Fold off-set welt in half lengthwise right sides together and overstretch corners, slash corners away, turn and press. Put decorative stitch along off-set welt on 0.5 cm off the edge. Apply fusing to pocket's location. Mark a line on off-set welt, determining the width of the off-set welt when ready. Topstitch small

- pocket bag on inner side of off-set welt. Put off-set welt on right side of front part to marker line (closer to center) right side downwards. Stitch off-set welt. Stitch big pocket bag to other marker line of pocket. Cut the pocket opening in the center between marker lines, making cross cuts to pocket marker corners. Turn lining of pocket onto wrong side. Straighten seam allowances and press. Sew edges of pocket bags, fixing corners of pocket. Topstitch short sides of pocket on 0.5 off the edge of off-set welt.
3. Sew side and shoulder edges. Press the seam apart. Sew lower collar into the neckline. Slash seam allowances and press apart.
  5. Sew sleeve seam, press seam allowances apart. Sew sleeve into armhole gathering slightly on rounded part.. Sew in shoulder pads and sleeve heads.
  6. Sew shoulder seams of back part neckline facings and of buttonstands, press seam allowances apart.
  7. Sew details of lining similar to main details, leaving a slit in side seam for turning out. Sew in top collar. Slash seam allowances and press apart. Stitch lining to buttonstands and back part facing. Press seam allowances onto lining.
  8. Fold lining and main detail right sides together and overstitch on buttonstands and collar. Fix seam allowances of top and lower collar together. Stitch lower edges of buttonstands to front part aslant to marked line of hem turning. Cut seams of lower corners of buttonstand. Overstitch lower edge of the coat. Turn the coat onto right side. Put decorative stitch on 0.7 cm off the edge of buttonstand and of collar.
  9. Stitch lining to hem of sleeves. Turn coat onto right side. Sew the slit.
  10. Serge 2 buttonholes on right front part, sew 4 buttons, sew inner button.
  11. Fold detail of the belt in half lengthwise right sides together and overstitch on long and one short sides. Turn belt onto right side, turn seam allowances of unsewn section inwards and put decorative stitch by 0.7 cm off the edge along the perimeter of the belt.

### **TECHNICAL DRAWING:**

