Jacket With Shaped Collar - Sewing Pattern #4005

Recommendations on fabric: soft wool or wool-blend fabrics (soft gabardine).



You will also need: fusible interfacing; 3 button; lining; shoulder pads.

Seam allowances: all seams 1 cm.

Note on seam allowances:
- If the pattern has double contour the seam allowances are included. They are 1 cm unless specified otherwise.
- If the pattern has single contour, the seam allowances are NOT included and need to be added when laying out the pattern.

Note on length of fabric:
Attention! The amount of fabric needed for your pattern is not included. It will depend on the selected pattern size, the width, and design of the fabric you plan to use. First, print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm). Measure how much fabric you will need. Don't forget to account for pieces that need to be cut multiple times and pieces that are cut on the fold.

CUTTING:

Note on cutting:
On the pattern pieces, “beam” means straight of grain. Lay out your pieces accordingly. Some pieces will be cut on the fold. This is noted on the pattern piece. Mark all notches and other design features such as pleats etc. from the pattern onto your fabric.
When sewing the garment, pay attention to notches, they must match up.

Main fabric:
1. Lower collar - cut 1
2. Upper collar – cut 1
3. Side front – cut 2
4. Side back – cut 2
5. Center back – cut 2
6. Center front – cut 2
7. Center front facing – cut 2
8. Back neck facing – cut 1
9. Back belt — cut 2
10. Front belt — cut 4

11. Sleeve – cut 2
12. Cuff — cut 2

Lining:
1. Center front – cut 2
2. Side back - cut 2
3. Center back – cut 2
4. Side front – cut 2
5. Sleeve – cut 2

Fusible interfacing:
1. Center front – cut 2
2. Center front facing – cut 2
3. Back neck facing – cut 1
4. Back belt — cut 1
5. Front belt — cut 2
6. Cuff — cut 2
7. Upper collar – cut 1

INSTRUCTIONS:

1. Apply fusible interfacing. Apply fusing on front along the lapel fold , its width should equal 1 cm (fusible interfacing).

2. Sew princess seams on front and back (sew side parts to center parts) and press towards center. Sew a decorative stitch at 0.9 cm from seam.

3. Sew the center back seam, press the seam apart. Sew and press apart shoulder and side edges of jacket.

4. Sew together the front belts and the back belts, pairwise. Press seams apart. Stitch the interfaced waistband pieces to the jacket. Press seams apart.

5. Sew and press the sleeve seam apart. Sew cuffs into a ring. Press seams apart. Cuffs turn right side out, press in half lengthwise and sew its outer edge to lower edge of sleeve. Press seams apart.

6. Sew sleeves into armholes matching notches, adjusting ease on sleeve cap. Sew shoulder pads.

7. Pin upper collar to lower collar and sew. Trim corners, turn right side out, straighten and press collar.

8. Sew seams on lining and sew in sleeves, leaving an opening in the right sleeve seam.

9. Sew and press apart the shoulder edges of the back neckline facing and of the center front facing. Sew lining to inner edges of the central front facings and to back neckline facing. Stitch the waistband pieces to the lower

edge of the lining. Press the seam towards the waistband.

10. Pin center front facing onto front right sides together, pin together and sew center front edge. When stitching make sure to place the front piece on top, sew from bottom towards top up to notch, that marks the end of collar seam. Trim the seam allowances at the upper corners of the lapels.

11. Sew the undercollar into the jacket neckline and the upper collar into the neckline of the back facing and center front facings. Press seam allowances of the collar seam apart and slipstitch them together close to the seam.

12. Sew lower edge of garment. Turn the jacket right side out, straighten seams and press. Stitch in the waistband attachment seam to secure the layers together. Sew a decorative stitch at 1 cm from the edge along the center front edge, of collar and of the lower edge of jacket.

13. Stitch the lining to the inner edge of the cuff. Press the seam towards the cuff. Turn jacket right side out through the opening in seam. Sew the opening in the sleeve closed. Stitch to secure the layers together into seam of cuff.

14. Make buttonholes on right front, and sew on buttons onto left front.

TECHNICAL DRAWING:

