

Sewing Pattern — Dress 4276

Recommendations on fabric: natural or mixed dress fabrics, contrast fabric for decoration.

You will also need: lining, blind zipper, fusing, two hooks with eyelets.

If the pattern has double contour the seam allowances are included.

If the pattern has single contour, the seam allowances are NOT included and need to be added when laying out and cutting details.

Seam allowance: all seams - 1 cm; hem of the dress – 2.0 cm; along the vent – 6 cm.

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



CUTTING:

Main fabric:

1. Upper back part - 2 details
2. Central back part - 2 details
3. Lower back part - 2 details
4. Upper front part – 1 detail
5. Central front part - 1 detail
6. Lower front part - 1 detail
7. Collar - 4 details

Lining:

1. Upper back part - 2 details
2. Upper front part – 1 detail

Fusing:

1. Collar - 2 details

INSTRUCTIONS:

1. Apply fusing to details of collar.
2. Sew darts on upper and lower details of back part. Press darts to center seam. Sew darts on upper and lower details of front part. Press waist darts towards center of the detail, bust darts - upwards. Overstitch lining details the same way.
3. Fold back part lining main fabric back part and overstitch edges of neckline and of armholes. Slash seam allowances on rounded parts, turn details right side out, press.
4. Fold details of collar right sides together and overstitch outer edge. Slash seam allowances on rounded parts, turn detail right side out, press. Stitch collar to front part neckline, putting it onto right side. Fix collar to front part along shoulder edges.
5. Slit upper front part and lining of upper front part along vertical line and cut out a hole according to marked line. The hole's lines are shown on the pattern! Fold lining of front part with front part and overstitch the neckline, vertical edge and decorative hole, inserting two hooks into front part vertical seam. Please note that allowance is 1 cm along neckline, and 0.5cm along vertical seam and the hole. Slash seam allowances on rounded parts, turn detail right side out, press. Overstitch edges of armholes. Slash seam allowances on rounded parts, turn details right side out, press.
6. Turn upper back part wrong side out, insert upper front part between main fabric and lining, level and sew shoulder edges. Turn back part right side out, straighten shoulder seam, press. Fold lining of back part onto wrong side, insert upper front part between main fabric and lining and sew side edges. Turn details right side out, straighten, press. Fix lining to center edge of back part and to lower edge and then sew as one detail.
7. Stitch lower back part to central one, press seam allowances upwards and serge. Stitch lower front part to central one, press seam allowances upwards and serge. Sew side seams, press seam onto back part and serge. Stitch upper front part to lower part, press seam allowances downwards and serge.
8. Cut off 5 cm on left lower back part along vertical edge of the vent. Apply fusing to wrong side of the vent on both details of lower back part. Mark center seam line (vent fold line) on the right side. Press left part along vent fold line, on right part press only seam allowance of right side of the vent (6 cm) onto wrong side. Align details along center seam and fix along top edge of the vent. Serge center edge of back part separately on each detail. Serge seam allowances of the vent. Sew center edge of back part from zipper notch up to vent corner. Slash away the corner of vent seam allowance on right part. Press apart seam allowances of the center seam, press seam allowances of the vent and fix them along right side with machine stitch. Sew in zipper. Turn inside the ends of the zipper tape near neckline and undersew.
9. Serge seam allowance of the dress hem, press onto wrong side and undersew with invisible stitches.
10. Fold vertical edge of front part line-on-line and sew eyelets according to hooks from the wrong side.

TECHNICAL DRAWING:

